

CERTIFICATION AND CLASSIFICATION		Evolution	
Type of flooring	EN 653		Resilient residential PVC floor covering
CE certification			yes
Classification	ISO 10874		Residential: 22
TECHNICAL CHARACTERISTICS		STANDARD	
Extreme protection PUR reinforcement			yes
Total thickness	ISO 24346		2,70 mm
Wear layer thickness	ISO 24340		0,20 mm
Total weight	ISO 23997		1,75 kg/m ²
Form of delivery - Rolls	ISO 24341		33 lm (15-33 lm) x 2,5/3/3,5/4m
Wear layer binder content			Type I
TECHNICAL PERFORMANCES		STANDARD	
Dimensional stability	ISO 23999		≤ 0,1%
Reaction to fire	ISO 13501-1		Cfl - s1; report N° 105/BP/09
Residual indentation	ISO 24343-1		≤ 0,35 mm
Impact sound reduction	ISO 717/2		18 dB
Underfloor heating			Suitable provided that the surface of the subfloor does not exceed 27°C
Fungi and bacteria resistance			Does not contribute to infection spreading
Castor chair test	ISO 4918		Very good
Light fastness	ISO 105 B02 - Method 3		7/8
Thermal resistance	DIN 52612		0,03-0,04 m ² K/W



	 EN 14041 : 2004 EN 13893 EN 1815 EN 12524	Manufactured by: Tarkett D.O.O. Industrijska zona 14 21400 Bačka Palanka SERBIA
--	--	---