

# PRODUCT DATASHEET LED BULKHEAD ROUND FH-20W/220E/R/840L

# Consumer Products Bulkhead Lamps| Bulkhead Round



## AREAS OF APPLICATION

- Garages
- Direct replacement for luminaires with fluorescent lamps
- Corridors, stairways, entrance areas
- General illumination

#### PRODUCT BENEFITS

- Low energy consumption and energy saving
- Suitable for use in dusty and damp locations thanks to high IP rating
- Instant 100 % light, no warm-up time
- No dark and yellow spots on the diffuser

#### PRODUCT FEATURES

- Surface mounted luminaires
- Type of protection: IP65
- Mounting screws and dowels included
- Lifetime: up to 25,000 h




## TECHNICAL DATA

## **Electrical data**

Rated wattage	20.00 W
Nominal wattage	20.00 W
Nominal voltage	185-240VAC
Operating frequency	5060 Hz
Power factor \( \lambda \)	> 0.50
Insulation Class	Class II

## Photometrical data


Rated luminous flux	1400 lm
Light color (designation)	Natural White
Color temperature	4000 K
Luminous flux	1400 lm
Color rendering index Ra	≥80
Standard deviation of color matching	≤4.8 sdcm
Luminous efficacy	70 lm/W
Rated color temperature	4000 K



# Light technical data

Starting time	< 0.5 s
Beam angle	220°

# Dimensions & weight



Diameter	220.0 mm
Height	70.0 mm
Product net weight	303.00 g

## Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	20000
Warranty	2 years

# Capabilities

Dimmable	No
LED module replaceable	Not replaceable
Protection class IK (shock resistance)	IK08

## **Temperatures & operating conditions**

Ambient temperature range	-25+40 °C
Storage temperature	-25+55 °C

## Additional product data

Installation method	Surface Ceiling / Wall		
Low flicker	Yes		
Mercury-free	Yes		
Product color	White		
Body material	Aluminum		
Cover material	Polycarbonate (PC)		
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value		
Mercury content	0.0 mg		
Standards	CE/CCC		

#### Order code/Name

Order code/Name	FH1870 LED BULKHEAD ROUND FH-20W/220E/R/840L

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
FH1870	Carton box 1	220 mm x 70 mm x 220 mm	232.00 g	3.38 dm³
FH1870	Shipping carton box 30	680 mm x 395 mm x 455 mm	11500.00 g	0.122 m³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping

#### **REFERENCES / LINKS**

For further products and actual information concerning LED luminaires see www.fucida.eu

For Guarantee see www.fucida.eu

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted.