

Caracteristici:

- * Motor fara perii, echipat cu frana de motor electronica (< 3s);
- * Diametrul discului 125mm
- * Suplu, usor, compact si aderent in zona de prindere (152mm)
- * Intrerupator cu alunecare (Slide)
- * Viteza variabila preselectabila;
- * Lampa indicator al starii de incarcare a bateriei
- * Constructie rezistenta la praf si apa;



Dial	No load speed (/min)	Use
1	4,700	 Grinding stainless steel  Rust or paint removal
2	5,500	
3	6,400	 Grinding, finishing  Rough grinding, cutting
4	7,200	
5	8,100	
6	9,000	



Specificatii

Diametrul discului G18DSLWP	125mm
Diametru prindere	22mm (7/8")
Ax portdisc	M14 x 2
Tensiune Baterie	18V
Turatie in gol	4700 - 9,000/min.
Lungime	326mm
Greutate	2,7 Kg
Accesorii Standard	Aparatoare, Cheie, Maner Lateral Cutie Carton

Baterii compatibile si timpi de incarcare

Baterie				Incarcator		
Voltaj	Tip	Capacitate*1	Fante racire	UC18YGSL UC18YKSL	UC18YRSL*2 UC18YFSL*2	UC18YML2*2 (AC/DC)*3
	BSL1820M	2.0Ah	●	60min.	30min.	30/80min
	BSL1840M	4.0Ah	●	120min.	60min.	60/160min
	BSL1850	5.0Ah	●	150min.	75min.	75/200min
	BSL36A18	5.0Ah	●	150min.	75min.	75/200min

*1 Valori nominale.

*2 Cu ventilator de racire.