

CERTIFICATION AND CLASSIFICATION		Absolut	
Type of flooring	EN 653		Resilient residential PVC floor covering
CE certification			yes
Classification	ISO 10874		Residential: 23 Commercial: 31
TECHNICAL CHARACTERISTICS		STANDARD	
Extreme protection PUR reinforcement			yes
Total thickness	ISO 24346		3,00 mm
Wear layer thickness	ISO 24340		0,45 mm
Total weight	ISO 23997		2,45 kg/m ²
Form of delivery - Rolls	ISO 24341		30 lm (15-30 lm) x 2,5/3m 25 lm (15-25 lm) x 3,5m 22 lm (15-22 lm) x 4m
Wear layer binder content			Type I
TECHNICAL PERFORMANCES		STANDARD	
Dimensional stability	ISO 23999		≤ 0,1%
Reaction to fire	ISO 13501-1		Cfl - s1
Residual indentation	ISO 24343-1		≤ 0,35 mm
Impact sound reduction	ISO 717/2		16 dB
Underfloor heating			Suitable provided that the surface of the subfloor does not exceed 27°C
Fungi and bacteria resistance			Does not contribute to infection spreading
Castor chair test	ISO 4918		Excellent
Light fastness	ISO 105 B02 - Method 3		7/8
Thermal resistance	DIN 52612		0,03-0,04 m ² K/W



	 	Manufactured by: Tarkett D.O.O. Industrijska Zona 14 21400 Bačka Palanka SERBIA
--	------------------	---