



# OAK CADENCE

## PRODUCT DETAILS

|                    |                                             |
|--------------------|---------------------------------------------|
| Article Number     | 13103AEK1PKW185                             |
| EAN Code           | 7393969107358                               |
| Surface treatment  | Matt lacquer                                |
| Dimensions         | 127 x 1860 mm                               |
| Weight per Package | 12.687 kg                                   |
| Area per Package   | 1.652 m <sup>2</sup>                        |
| Area per pallet    | 104.076 m <sup>2</sup>                      |
| Package info       | Packages may contain start and stop boards. |

## DETAIL DESCRIPTION

Even color with minor variations. Small to medium sized knots in limited numbers allowed.

## COLOUR CHANGE

Stained product - noticeable color change over time.

## FACTS

|                      |                     |
|----------------------|---------------------|
| Wood Species         | Oak                 |
| Design               | 1-strip             |
| Grading              | Variation           |
| Range                | Kährs Avanti        |
| Collection           | Canvas Collection   |
| Resandable           | 2-3 times           |
| Natural/Stained      | Stained             |
| Brinell Value        | 3,7                 |
| Joint                | Woodloc® 5G         |
| Floor heating        | Yes                 |
| Warranty             | 25 years            |
| Warranty US          | 25 years            |
| Wear-layer material  | Hardwood            |
| Wear Layer Thickness | 3 mm                |
| Core material        | Pine/Spruce lamella |
| Thickness            | 13 mm               |
| Installation method  | Floating, Glue-down |
| Surface Colour       | White               |

## TECHNICAL PROPERTIES

|                                        |                        |             |
|----------------------------------------|------------------------|-------------|
| Moisture content                       | EN13183                | 7%±2%       |
| Minimum Mean Density kg/m <sup>3</sup> | >500 kg/m <sup>3</sup> |             |
| Reaction To Fire                       | EN13501-1              | Dfl-s1      |
| Formaldehyde Emission                  | EN717-1                | E1          |
| Content PCP                            | CEN/TR14823            | ≤ 5 x 10-6n |
| Breaking Strength N/mm <sup>2</sup>    | EN1533                 | NPD         |
| Thermal Conductivity                   | EN12664                | 0,08 W/mK   |
| Thermal Resistance R-Value             | .15 (m2K/W)            |             |
| Biological Durability                  | EN350-2                | Class 1     |
| CARB2                                  | Compliant              |             |
| Slipperiness                           | CEN/TS15676            | NPD         |

Other products in this collection



Oak Fawn



Oak Henna



Oak Heather



Oak Cadence



Oak Reiter



Oak Muse



Oak Curio



Oak Carbon



Oak Etch



Oak Tuft



Oak Mostra

CERTIFICATES



Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*