

# Technical Data Sheet

Rust-Oleum Frosted Glass (400ml Aerosol) Matt Finish

---

**Create a translucent frosted glass effect on transparent surfaces including glass doors, windows, skylights and greenhouses. For a decorative effect, use with stencils to create a beautiful etched glass look on mirrors, glass accessories and more.**

**Preparation:** Ensure surfaces to be painted are free from wax, oil and grease. Cover surrounding areas to protect from spray mist.

## **Interior use only**

**Application:** Shake can vigorously for 1 minute after mixing ball begins to rattle, continue to shake regularly during use. Hold can 30cm from surface and spray in a steady back and forth motion, slightly overlapping with each stroke. For best results whilst spraying keep the can the same distance from the surface and keep the can in motion. Apply 1-2 coats, overcoating after 20 minutes.

**Cleaning:** To clear spray for future use, turn can upside down and spray until clear gas is emitted.

**Drying & Recoating:** Touch dry in 10 minutes. Recoat after 20 minutes.

Drying times are based on warm (15°C), dry application conditions with good ventilation. Lower temperatures and higher humidity will prolong the drying times.

**Coverage:** A 400ml can covers approximately 2.5m<sup>2</sup> dependent upon surface profile / porosity.

**Limitations:** Frosted surfaces may be cleaned with a soft cloth or be hand washed. Do not place in a dishwasher. To remove the frosted finish use acetone or lacquer thinner. Apply only when temperature is between 10-32°C and relative humidity below 85%.

Special Precautions should be taken during the surface preparation of pre 1960's paint surfaces over wood and metal as they may contain harmful lead. When dry-sanding avoid dust inhalation by wearing a suitable protective face mask. A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. For further information please contact our Technical Services Department.

**Shelf Life:** 3 years (unopened) from date of manufacture. (See base of can).

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.