

Rockfon® Sofit®

Datasheet



Rockfon® Sofit®

- Plain pre-painted white fleece
- Class C sound absorption lightweight tile
- Basic A-edge tile available in standard 600 X 600 dimension
- Easy to clean with a vacuum

Product Description

- Stone wool tile

- Visible side: plain pre-painted white fleece

Application Areas

- Office

-	Retail	

Edge detail	Module size (mm)	Weight (kg/m²)	MS / MS easy access (mm)	Recommended installation system
A15	600 x 600 x 12	1,6	50 / 100	Rockfon® System T15 A™
	600 x 600 x 15	1,8	50 / 100	Rockfon® System T15 A™
A24	600 x 600 x 12	1,6	50 / 100	Rockfon® System T24 A™
	600 x 600 x 15	1,8	50 / 100	Rockfon® System T24 A™

MS = Minimum suspension MS easy access = Minimum suspension - tiles demountable




Performance



Sound absorption α_{w} : up to 0,65 (Class C)

Thickness (mm) /



Suspension (incl. tile - mm)	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	α_{w}	Ab	NRC
12 / 62	0.05	0.30	0.70	0.95	0.95	0.95	0.60	С	0.75
15 / 60	0.10	0.35	0.80	1.00	0.95	0.95	0.65	С	0.75



Reaction to fire



Humidity and sag resistance Up to 100% RH. No visible deflection in high humidity



Cleaning

Vacuum



Hygiene

Stone wool provides no sustenance to microorganisms



Environment

Fully recyclable stone wool The recycled content of Rockfon products is between 29% and 64% according to ISO 14021.



Carbon footprint

1.96 - 2.04 kg of CO2 eq. (cradle to gate based on EPD)



Indoor environment

A selection of Rockfon products have been awarded the Finnish M1 emission classification for building materials and the Danish Indoor Climate Label for low emission products



pinterest.dk/Rockfon

youtube.com/RockfonOfficial

facebook.com/RockfonOfficial

instagram.com/Rockfon_Official

Sounds Beautiful

Rockfon

ROCKWOOL, a. s. Cihelní 769 735 31 Bohumín 3 Czech Republic

Tel. (+420) 606 618 443

www.rockfon.cz info@rockfon.cz

