

Technical Data Sheet

Rust-Oleum Rust Reformer (400ml spray):
Black

Apply direct to rusted metal to create a ready-to-paint surface without the need for sanding. Prevents further rusting.

Preparation: Ensure surfaces to be painted are free from loose paint, rust, wax, oil and grease. Previously painted surfaces should be abraded to provide a key. Cover surrounding areas to protect from spray mist.

Application: Shake can vigorously for 1 minute after mixing ball begins to rattle, continue to shake regularly during use. Hold can 30cm from surface and spray in a steady back and forth motion, slightly overlapping with each stroke. For best results whilst spraying keep the can the same distance from the surface and keep the can in motion. Apply several light coats a few minutes apart.

Cleaning: After use invert can and spray for 2-3 seconds to clear the spray nozzle.

Drying & Recoating: Touch dry in 20 minutes. Hard dry 24 hours. One coat of Rust Reformer is sufficient. Allow to dry for 24 hours if applying top coats. 1-2 coats recommended.

Coverage: A 400ml can covers approximately 2m² per coat dependent upon surface profile / porosity.

Limitations: Apply only when temperature is between 10-32°C and relative humidity below 85%.

Special Precautions should be taken during the surface preparation of pre 1960's paint surfaces over wood and metal as they may contain harmful lead. When dry-sanding avoid dust inhalation by wearing a suitable protective face mask. A copy of the appropriate Health & Safety should be consulted prior to use. For further information please contact our Technical Services Department.

Shelf Life: 3 years (unopened) from date of manufacture. (See base of can).

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.