

Technical Data Sheet

Rust-Oleum Low Tack Adhesive (150ml Aerosol) Clear Finish

A repositionable, low tack adhesive that provides a temporary bond for lightweight materials.

Preparation: Ensure surfaces to be bonded are clean, dry and free from oil and grease. Test for suitability on an inconspicuous area before using on new applications.

Application: Shake can thoroughly before and during use. Spray adhesive onto one surface only, hold can approximately 25-30cm from the surface and spray with light, even strokes. Allow to dry until tacky before pressing both surfaces together. To reposition the material gently pull from one corner lifting away from the surface and reposition as necessary.

Cleaning: After use invert can and spray for 2-3 seconds to clear the spray nozzle.

Drying: 10 minutes.

Coverage: A 150ml can covers approximately 0.75m² per coat dependent upon surface profile / porosity.

Limitations: For use only as a repositionable spray mount adhesive. Not suitable for plasticised PVC or expanded polystyrene.

Shelf Life: 3 years (unopened) from date of manufacture. (See base of can).

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK.

Technical Services Department: 0191 410 6611

E-mail: info@tor-coatings.com www.tor-coatings.com or www.rustoleumspraypaint.com

warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK.
Technical Services Department: 0191 410 6611
E-mail: info@tor-coatings.com www.tor-coatings.com or www.rustoleumspaypaint.com

03/02/2016