

Technical data sheet Depth Gauge Bead 6 mm, galvanized Ú¦[-ÃÁ @ãaæÁ^} &ÁØ^ÐZ} Á {

Provide a quick and accurate means of ensuring consistent, minimum plaster depths as plaster is simply 'ruled off' to leave the required thickness. Made of punched and galvanized steel, they are used to create a smooth finish for example before tiling and are available for different plaster thicknesses.

Should the plaster and beads be exposed to constant high moisture or damp after installation in e.g. wet rooms, swimming pools or bathrooms, it is advisable to use corrosion free material such as stainless steel.

Technical Data:

Galvanized steel products are manufactured according to BS EN 10346:2009-DX51+Z275 and EN 13658-1:2005 and have a double sided zinc coating of at least 275g/m².

Bead Measurements:

21/6 mm



Product specification:					
Description:	Depth Gauge				
Item number:	4100 – 200 CM	4100 – 250 CM	4100 – 260 CM	4100 – 275 CM	4100 – 300 CM
Plaster thickness:	6 mm				
Material:	Galvanized Steel				
Unit:	50 pieces á 200 cm = 100 meters	50 pieces á 250 cm = 125 meters	50 pieces á 260 cm = 130 meters	50 pieces á 275 cm = 137,5 meters	50 pieces á 300 cm = 150 meters
GTIN Pack: GTIN Piece:	40 228420 0164 5 40 228420 0695 4	40 228420 0165 2 40 228420 0696 1	40 228420 0166 9 40 228420 0697 8	40 228420 5699 7 40 228420 1899 5	40 228420 0167 6 40 228420 0698 5

DOP 4100 P31 Reaction to fire Class A1 Customs tariff no. 7314 50 00



EJOT Romania

Şos. Comercială nr. 21 A, DN 65 B,Com.Bradu, Sat Geamăna,Jud. Argeș

Phone: +40 248 2238 – 86 Fax: +40 248 2238 - 84 E-mail:infoRO@ejot.com Internet: http://www.ejot.ro Installation according to Europrofiles leaflet "Planning and application of metal beads"

Care has been taken to ensure that the contents of this publication are accurate, but Tata Steel Europe Limited and its subsidiaries, which includes Tata Steel UK Limited, do not accept responsibility or liability for errors or information that is found to be misleading. Before using products or services supplied or manufactured by Tata Steel Europe Limited and its subsidiaries, customers should satisfy themselves as to their suitability.