

Unghi (°)	DN1 (mm)	DN2 (mm)	L (mm)	e (mm)	Cod (*PBC)
45	110	110	274,6	3,4	CF245110110
45	125	110	297	3,2	CF245125110
45	125	125	308,1	3,4	CF245125125
45	160	110	384,6	4,2	CF245160110
45	160	125	349	4	CA245160125
45	160	160	384,6	4,2	CF245160160
45	200	110	474,3	5,1	CF245200110
45	200	125	394	4,9	CA245200125
45	200	160	474,3	5,1	CF245200160
45	200	200	474,3	5,1	CF245200200
45	250	110	482	6,2	CA245250110
45	250	125	484	6,2	CA245250125
45	250	160	487	6,2	CA245250160
45	250	200	536	6,2	CA245250200
45	250	250	603	6,2	CA245250250
45	315	110	515	7,7	CA245315110
45	315	125	515	7,7	CA245315125
45	315	160	580	7,7	CA245315160
45	315	200	580	7,7	CA245315200
45	315	250	633	7,7	CA245315250
45	315	315	723	7,7	CA245315315
45	400	160	545	9,8	CA145400160*
45	400	200	598	9,8	CA145400200*
45	400	250	808	9,8	CA145400250*
45	400	315	899	9,8	CA145400315*
45	400	400	1019	9,8	CA145400400*
45	500	160	714	12,3	CA145500160*
45	500	200	770	12,3	CA145500200*
45	500	250	841	12,3	CA145500250*
45	500	315	932	12,3	CA145500315*
45	500	400	1052	12,3	CA145500400*
45	500	500	1193	12,3	CA145500500*
45	630	315	967	15,4	CA145630315*
45	630	400	1086	15,4	CA145630400*
45	630	500	1229	15,4	CA145630500*

45	630	630	1412	15,4	CA145630630*
87.5	110	110	236,6	3,4	CF290110110
87.5	125	110	297	3,2	CA290125110
87.5	125	125	264,1	3,4	CF290125125
87.5	160	110	327,6	4,2	CF290160110
87.5	160	125	300	4	CA290160125
87.5	160	160	327,6	4,2	CF290160160
87.5	200	110	403,3	5,1	CF290200110
87.5	200	125	335	4,9	CA290200125
87.5	200	160	403,3	5,1	CF290200160
87.5	200	200	403,3	5,1	CF290200200
87.5	250	110	433	6,2	CA290250110
87.5	250	125	433	6,2	CA290250125
87.5	250	160	433	6,2	CA290250160
87.5	250	200	518	6,2	CA290250200
87.5	250	250	508	6,2	CA290250250
87.5	315	110	496	7,7	CA290315110*
87.5	315	125	495	7,7	CA290315125
87.5	315	160	496	7,7	CA290315160
87.5	315	200	496	7,7	CA290315200
87.5	315	250	612	7,7	CA290315250*
87.5	315	315	611	7,7	CA290315315
87.5	400	160	595	9,8	CA190400160*
87.5	400	200	645	9,8	CA190400200*
87.5	400	250	695	9,8	CA190400250*
87.5	400	315	745	9,8	CA190400315*
87.5	400	400	795	9,8	CA190400400*
87.5	500	160	608	12,3	CA190500160*
87.5	500	200	648	12,3	CA190500200*
87.5	500	250	688	12,3	CA190500250*
87.5	500	315	788	12,3	CA190500315*
87.5	500	400	888	12,3	CA190500400*
87.5	500	500	988	12,3	CA190500500*
87.5	630	315	796	15,4	CA190630315*
87.5	630	400	881	15,4	CA190630400*
87.5	630	500	981	15,4	CA190630500*
87.5	630	630	1111	15,4	CA190630630*