



Product Data Sheet Bold

January, 2025

Type of flooring	EN ISO 26986	Expanded (cushioned) polyvinyl chloride floor covering			
Class of use	ISO 10874 (EN 685)				
CE certification	EN 14041:2004/AC:2006	2701-0112-DoP-2025-01			
TECHNICAL CHARACTERISTICS AND PERFORMANCES					
	ISO 24346 (EN 428) Total tickness	2,00 mm		ISO 24341 (EN 426) Roll lenght Roll width	30m (15-30) 25m (15-25) 2,5; 3; 4m
	ISO 24340 (EN 429) Wear layer tickness	0,40 mm		ISO 717/2 Impact sound absorption	17 dB
	ISO 23997 (EN 430) Weight per m ²	1,80 kg/m ²		ISO 24343-1 (EN 433) Residual indentation	≤ 0,20 mm
	ISO 105 B02 Method 3 Light fastness	≥ 6		ISO 4918 (EN 425) Castor chair	pass
	ISO 23999 (EN 434) Dimensional stability	Requirement by standard:< 0,4 % Tarkett result: ≤ 10,011 %		Underfloor heating Suitable provided that the surface of the subfloor does not exceed 27°C	
	EN 1815 Static electrical propensity	≤ 2 kV (antistatic)		EN 13893 Slip resistance	
	EN 13501-1 Fire classification	Bfl-s1		EN 12524 Thermal resistance	0,02 - 0,03m ² /kW
Wear layer binder content ISO 11638		Type I	DIN 51130 Ramp test		R10



2701-0112-DoP-2025-01