

Technical Data Sheet

Rust-Oleum Glitter Rainbow (150ml Spray)

A quick drying, non-yellowing, decorative topcoat containing glitter particles, perfect for adding a special touch to craft & hobby projects.

Preparation: Surfaces to be painted should be clean, dry and free from loose paint, rust, wax, oil and grease. Previously painted surfaces should be abraded to provide a key. Cover surrounding areas to protect from over spray.

Application: Shake can vigorously for 1 minute after mixing ball begins to rattle, continue to shake regularly during use. Hold can 30cm from surface and spray in a steady back and forth motion, slightly overlapping with each stroke. For best results whilst spraying keep the can the same distance from the surface and keep the can in motion. Apply several light coats a few minutes apart.

Cleaning: After use invert can and spray for 2-3 seconds to clear the spray nozzle.

Drying & Recoating: Touch dry in 15 minutes. Recoat after 30 minutes. Drying times are based on warm (15°C), dry application conditions with good ventilation. Lower temperatures and higher humidity will prolong the drying times. 1-2 coats recommended.

Coverage: A 150ml can covers approximately 0.75m² dependent upon surface profile/porosity.

Limitations: Do not use on surfaces that regularly exceed temperatures over 80°C. Apply only when temperature is between 10-32°C and relative humidity below 85%. Special precautions should be

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK.

Technical Services Department: 0191 410 6611

E-mail: info@tor-coatings.com www.tor-coatings.com or www.rustoleumspraypaint.com

taken during the surface preparation of pre 1960's paint surfaces over wood and metal as they may contain harmful lead. When dry-sanding avoid dust inhalation by wearing a suitable protective face mask. A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product.

Shelf Life: 3 years (unopened) from date of manufacture. (See base of can).

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.

Tested to BS EN 71-3: 2013 + A1: 2014 Safety of Toys. Migration of Certain Elements.