




**TECHNICAL DATA SHEET**
**FLOORPAN**  
 WINGS

**8 MM - CLASS 33 - AC5**

THICKNESS	mm	8	EN 13329+A1
WIDTH	mm	197	EN 13329+A1
LENGHT	mm	1205	EN 13329+A1
SURFACE		Sky	
EUROPEAN STANDARD	-	  	EN13329
<b>PACKAGE DETAILS</b>			
PIECE	8 piece / 1 package		
M <sup>2</sup>	1,9 m <sup>2</sup>		
KG	14 kg		
<b>PALLET DETAILS</b>			
PIECE	60 package / 1 pallet		
M <sup>2</sup>	113,9 m <sup>2</sup>		
KG	855 kg		
CLASS	-	33	EN 13329+A1
ABRASION RESISTANCE	-	AC5	EN 13329+A1
THICKNESS SWELLING	%	≤15	ISO 24336
RESISTANCE TO IMPACT	SMALL BALL	N	EN 13329+A1
	LARGE BALL	mm	
WARRANTY DOMESTIC / COMMERCIAL	Years	25/15	-
RESISTANCE TO STAINING	-	Min. 5 (group 1 and 2) Min. 4 (group 3)	EN 438-2_5
SURCAFE SOUNDNESS	N/mm <sup>2</sup>	≥1.25	EN 13329+A1
LOCK STRENGTH	LENGHT	kN/m	ISO 24334
	WIDTH	kN/m	
EFFECT OF CASTOR CHAIR <sup>a</sup>	25.000 Cycles	No Damage	EN 425:2002
EFFECT OF A FURNITURE LEG	-	No Damage	EN 424
OPENING BETWEEN ELEMENTS. (O)	mm	≤0,20	EN 13329+A1
HEIGHT DIFFERENCE BETWEEN ELEMENTS, (H)	mm	≤0,15	EN 13329+A1
MOISTURE CONTENT	%	4-10	EN 322
FIRE RESISTANCE	Class	C <sub>f</sub> S1	EN 9239-1
FORMALDEHYDE RELEASE	mg/m <sup>2</sup> h	≤3,5 (E1)	EN 12460-3
SLIP RESISTANCE	Class	-	EN 13893:2003
IMPACT SOUND REDUCTION	dB	15	EN ISO 10140-3
THERMAL RESISTANCE	(m <sup>2</sup> K)/W	0,0614	EN 12667:2001