

# Technical Data Sheet

Rust-Oleum Stained Glass Paint (150ml Aerosol):  
Red, Green & Blue

---

**A fast drying acrylic spray paint for interior glass.**

**Preparation:** Surfaces to be painted should be clean, dry and free from oil and grease. Cover surrounding areas to protect from spray mist.

**Application:** Shake can vigorously for 1 minute after mixing ball begins to rattle, continue to shake regularly during use. Hold can 30cm from surface and spray in a steady back and forth motion, slightly overlapping with each stroke. For best results whilst spraying keep the can the same distance from the surface and keep the can in motion. Apply several light coats a few minutes apart.

**Cleaning:** After use invert can and spray for 2-3 seconds to clear the spray nozzle.

**Drying & Recoating:** Touch dry in 15 minutes. Recoat after 20 minutes.

**Coverage:** A 150ml can covers approximately 0.75m<sup>2</sup> dependent upon surface profile / porosity.

**Limitations:** Not resistant to cleaning with dishwashers, use warm soapy water only. Do not use on surfaces that regularly exceed temperatures over 80°C.

**Shelf life:** 3 years (unopened) from date of manufacture. (See base of can).

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK.  
**Technical Services Department: 0191 410 6611**  
E-mail: [info@tor-coatings.com](mailto:info@tor-coatings.com) [www.tor-coatings.com](http://www.tor-coatings.com) or [www.rustoleumspraypaint.com](http://www.rustoleumspraypaint.com)

03/02/2016