



5.1.5 PN25 (SDR5) STABLE Pipe, PP-R with Aluminum for Hot & Cold Water

| PRODUCT PICTURE | ITEM CODE | SIZE (MM) | M/PACK | $D_{1,MM}$ | $D_{2,MM}$ | S | S_1 | $S_{2,MM}$ | TECHNICAL DRAWING |
|---|---|------------|--------|------------|------------|------|-------|------------|---|
|  | 111.1B.A21.E04 | 20 x 3.4 | 100 | 20.0 | 21.5 | 3.4 | 0.20 | 1.1 |  |
| | 111.1B.A21.F04 | 25 x 4.2 | 100 | 25.0 | 26.5 | 4.2 | 0.20 | 1.1 | |
| | 111.1B.A21.G04 | 32 x 5.4 | 60 | 32.0 | 33.5 | 5.4 | 0.20 | 1.1 | |
| | 111.1B.A21.H04 | 40 x 6.7 | 60 | 40.0 | 41.5 | 6.7 | 0.20 | 1.1 | |
| | 111.1B.A21.I04 | 50 x 8.3 | 40 | 50.0 | 51.5 | 8.3 | 0.20 | 1.1 | |
| | 111.1B.A21.J04 | 63 x 10.5 | 28 | 63.0 | 64.5 | 10.5 | 0.20 | 1.1 | |
| | 111.1B.A21.K04 | 75 x 12.5 | 20 | 75.0 | 76.5 | 12.5 | 0.25 | 1.05 | |
| | 111.1B.A21.L04 | 90 x 15.0 | 12 | 90.0 | 91.5 | 15.0 | 0.25 | 1.05 | |
| | 111.1B.A21.M04 | 110 x 18.3 | 8 | 110.0 | 111.5 | 18.3 | 0.25 | 1.05 | |
| | <p>VESBO STABLE Pipes are preferred mainly for exposed pipe installations attributed to low linear expansion rate and reinforced structure.</p> | | | | | | | | |