

PILA LED Panels

Specifications

80

CRI



220-240 Vac



35,000h



non dimmable

**PILA RC007B LED40S/840
PSU I W60L60 NOC**



**PILA RC007B LED40S/840
PSU I W60L60 OC**



Lamp type	LED Panel	LED Panel
Light output (lm)	4000	4000
Power (W)	40	40
CCT (K)	4000	4000
IP / IK	IP20	IP20
UGR	<25	<19
Safety Class	Class I	Class I
EAN1	8719514959972	8719514959989
12NC	911401879584	911401879684



RC007Z SME-2 Pila

Aplică cu montaj pe perete sau tavan

WL007C

Ceiling RD

- Montare pe perete sau pe tavan
- IP 65 (versiune fără senzor) / IP 54 (versiune cu senzor)
- Oval (OVL) sau rotund (RND)
- Interval temperatură ambientală: de la -25 la +40 °C
- Unghi de detectare 90 °
- Disponibil și cu senzor de mișcare HF (MDU)



GEN 1



GEN 2



4000 K



35 000 h (L70)



NON-DIMABIL



IP65



IP54



IK06

CU SENZOR



4000 K



15 000 h (L70)



NON-DIMABIL



IP20

Cod	EAN	Descriere produs	Putere nominală W	Flux luminos lm	Temperatura de culoare K
911401735132	871016333510099	PILA WL007C LED13S/840 PSU OVL WH	15	1.400	4.000
911401735142	871016333511799	PILA WL007C LED14S/840 PSU RND MDU WH	15	1.300	4.000
911401774752	871016336442199	PILA WL007C LED12S/840 PSU RND WH G2	12	960	4.000
911401774762	871016336443899	PILA WL007C LED20S/840 PSU RND WH G2	20	1.600	4.000
915005778323	872790096780700	PILA Ceiling RD 10W 4000K W 06	10	1.100	4.000
915005778923	872790096782100	PILA Ceiling RD 17W 4000K W 06	17	1.700	4.000



PILA Downlights



Product description	System power (W)	CCT (K)	Light output (lm)	CRI	LifeTime L70B50 (h)	EAN1	12NC
PILA DN020B LED13/830 14W D150 RD EU	14	3000	1300	80	20,000	8727900967845	929002668382
PILA DN020B LED13/840 14W D150 RD EU	14	4000	1300	80	20,000	8727900967869	929002668482
PILA DN020B LED22/830 22.5W D200 RD EU	22.5	3000	2200	80	20,000	8727900967883	929002668682
PILA DN020B LED22/840 22.5W D200 RD EU	22.5	4000	2200	80	20,000	8727900967906	929002668782

Corp de iluminat etanș

WT007C

- Eficiență ridicată (100 lm / W)
- Clasa de protecție I
- Interval temperatură ambientală: de la -20 la +35 °C
- Dimensiuni compacte - lățimea corpului doar 36 mm, înălțimea 45 mm



4000 K



35 000 h (L70)



NON-DIMABIL



IP65



IK06

Cod	EAN	Descriere produs	Putere nominală W	Flux luminos lm	Temperatura de culoare K
911401735772	871016333514899	PILA WT007C LED34S/840 PSU L1200	34	3.400	4.000
911401735782	871016333515599	PILA WT007C LED54S/840 PSU L1500	54	5.400	4.000
911401809680	871016334311299	PILA WT007C LED17S/840 PSU L600	17	1.700	4.000

PILA spotlights



Product description	Luminous flux lm	Power W	Color temperature K	Motion sensor	IP protection	Contact protection class	GPC	EOC
PILA BVP008 10W 3000K	900	10	3000	no	IP65	I	911401810583	871951453304299
PILA BVP008 10W 4000K	950	10	4000	no	IP65	I	911401820583	871951453298499
PILA BVP008 20W 3000K	1,800	20	3000	no	IP65	I	911401811583	871951453303599
PILA BVP008 20W 4000K	1,900	20	4000	no	IP65	I	911401821583	871951453297799
PILA BVP008 50W 3000K	4,500	50	3000	no	IP65	I	911401814583	871951453301199
PILA BVP008 50W 4000K	4,750	50	4000	no	IP65	I	911401824583	871951453295399
PILA BVP008 100W 4000K	9,500	100	4000	no	IP65	I	911401826583	871951453294699
PILA BVP008 200W 4000K	19,000	200	4000	no	IP65	I	911401828583	871951453293999

PILA spotlights (MDU variants)



Product type	Luminous flux lm	Power W	Color temperature K	Motion sensor	IP protection	GPC	EOC
PILA BVP008 20W 4000K MDU	1,800	20	4000	Yes	IP65	911401874983	871951453461299
PILA BVP008 50W 4000K MDU	4,500	50	4000	Yes	IP65	911401875583	871951453457599

PILA LED Highbay – G2

Specifications

**PILA BY007P G2
LED100S/840 PSU WB**



**PILA BY007P G2
LED150S/840 PSU WB**



**PILA BY007P G2
LED200S/840 PSU WB**



Product type	LED Highbay G2	LED Highbay G2	LED Highbay G2
Light output (lm)	10000	15000	20000
System power (W)	100	150	200
CCT (K)	4000	4000	4000
IP / IK	IP65/IK06	IP65/IK06	IP65/IK06
Safety Class	Class I	Class I	Class I
EAN1	8719514958630	8719514958647	8719514958654
12NC	911401877884	911401877984	911401878084

Corp de iluminat tip baghetă

BN007C

- Eficiență ridicată (100 lm / W)
- Clasa de protecție I
- Gamă largă de aplicații



Cod	EAN	Descriere produs	Putere nominală W	Flux luminos lm	Temperatura de culoare K
911401735772	871016333514899	PILA WT007C LED34S/840 PSU L1200	34	3.400	4.000