

Technical Data Sheet

Rust-Oleum Direct to Vinyl (Aerosol) Black Gloss

A flexible paint designed to restore colour to vinyl and fabric. Made with actual vinyl paint resins for maximum durability. Ideal for car seats, upholstery and more.

Preparation: Clean surface to be painted with soap and water, rinse with clean water and allow to dry. Cap and / or label indicate approximate colour and finish. Cover surrounding areas to protect from spray mist.

Application: Shake can vigorously for 1 minute after mixing ball begins to rattle, continue to shake regularly during use. Hold can 30cm from surface and spray in a steady back and forth motion, slightly overlapping with each stroke. For best results whilst spraying keep the can the same distance from the surface and keep the can in motion. Apply several light coats a few minutes apart.

Cleaning: After use invert can and spray for 2-3 seconds to clear the spray nozzle.

Drying & Recoating: Touch Dry in 20 minutes. Hard Dry in 24 hours. Recoat within 1 hour or after 24 hours.

Coverage: This can covers approximately 2m² per coat dependent upon surface profile / porosity.

Limitations: Do not use on galvanised steel or surfaces that regularly exceed temperatures over 90°C. Apply only when temperature is between 10-32°C and relative humidity below 85%. Special Precautions should be taken during the surface preparation of pre 1960's paint surfaces over wood and metal as they may contain harmful lead. When

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK.

Technical Services Department: 0191 410 6611

E-mail: info@tor-coatings.com www.tor-coatings.com or www.rustoleumspraypaint.com

dry-sanding avoid dust inhalation by wearing a suitable protective face mask. For further information please contact our Technical Services Department.

Shelf Life: 3 years (unopened) from date of manufacture. (See base of can).

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.