



Zalakerámia

Data sheet

| | | | |
|------------------|-----------------------------------|----------------|-------------|
| Type of product: | glazed | ceramic tile | dry pressed |
| Norm: | EN 14411 Annex G E≤0,5% Bla group | | |
| Glaze: | glazed | | |
| Surface: | matt | | |
| Product line: | Tree | greise port | |
| Catalogue code: | ZGD 62083 | 6064-0188-4201 | |
| Normal size: | 20x60x0,83 cm | | |

| | |
|------------|-----------|
| 600x200 mm | Kaliber 0 |
| 599x200 mm | Kaliber 9 |
| 598x199 mm | Kaliber 8 |
| 597x199 mm | Kaliber 7 |
| 596x199 mm | Kaliber 6 |
| 595x198 mm | Kaliber 5 |
| 601x200 mm | Kaliber 1 |
| 602x201 mm | Kaliber 2 |
| 603x201 mm | Kaliber 3 |
| 604x201 mm | Kaliber 4 |

| <i>essential characteristics</i> | <i>inspection method</i> | <i>nominal value</i> | <i>Zalakerámia production</i> |
|---|--------------------------|---------------------------|-------------------------------|
| length and width | ISO 10545-2 | ± 0,6% | ± 0,3% |
| thickness | ISO 10545-2 | ± 5% | ± 3,0% |
| rectangularity | ISO 10545-2 | ± 0,5% | ± 0,3% |
| straightness of edges | ISO 10545-2 | ± 0,5% | ± 0,25% |
| curvature of edges | ISO 10545-2 | ± 0,5% | + 0,3% |
| centre curvature | ISO 10545-2 | ± 0,5% | + 0,3% |
| water absorption | ISO 10545-3 | E ≤ 0,5% | average 0,3% |
| bending strength N/mm ² | ISO 10545-4 | min. 35 | average 36 |
| thermal shock resistance | ISO 10545-9 | required | as per norm |
| resistance against patch-makers | ISO 10545-14 | min. 3. Sort. | as per norm |
| chemical resistance against household chemicals | ISO 10545-13 | min. GB | as per norm |
| resistance against pool chemicals | ISO 10545-13 | min. GB | as per norm |
| wear resistance | ISO 10545-7 | indicated by manufacturer | PEI 4 |
| frost resistance | ISO 10545-12 | required | frost resistant |
| anti-slip property | DIN 51130/1991 | not required as EU norm | NPD |

Hereby we confirm, that above mentioned product complies with rules of EN 14411 norm.
Tófej, 06. 08. 2021

ZALAKERÁMIA ZRT.

ZALAKERÁMIA ZÁRTKÖRŰEN MŰKÖDŐ RÉSZVÉNYTÁRSASÁG
8946 Tófej Rákóczi út 44. Pf.: 1. Telefon: (92) 566 400, Fax: (92) 369 070
Budapesti Iroda: 1239 Budapest, Grassalkovich út 255. Tel.: (1) 289 5101, Fax: (1) 286 0183