

FAIANTA 30186-A-TV EVIA CREM 30X60 CM - GLAZURATA INTERIOR RECTIFICATA MATA
FAIANTA 30186-B-TV EVIA MARO 30X60 CM - GLAZURATA INTERIOR RECTIFICATA MATA
FAIANTA 30186-HL-TV EVIA 30X60 CM - GLAZURATA INTERIOR RECTIFICATA MATA
GRESIE 30186-BF EVIA MARO 30X30 CM - GLAZURATA INTERIOR RECTIFICATA MATA

au urmatoarele caracteristici comunicate de producator:

QUALITY CERTIFICATE REPORT

No.	PROPERTIES	REQUIREMENTS ISO 10545	RESULT
1	Size (%)	Length: ± 0.50	+0.06
		Width: ± 0.50	+0.02
2	Thickness (%)	± 10	± 1.05
3	Straightness of sides (%)	± 0.30	-0.04 ~ +0.05
4	Rectangularity (%)	± 0.50	-0.05 ~ +0.04
5	Center curvature (%)	± 0.30	+ 0.05
6	Edge curvature	± 0.30	+ 0.06
7	Warpage (%)	± 0.50	+ 0.05
8	Surface quality	95	95
9	Water absorption (%)	average $10 < E < 20$	9
10	Breaking strength (N)	If thickness $\geq 7.5\text{mm}$, Average ≥ 600 ,	809.38
11	Modulus of rupture (Mpa)	Average ≥ 15 , individual ≥ 12	16.59
12	Thermal shock resistance 15/145° C	10 Cycle Pass	Passed
13	Resistance to house hold chemical reagent	Not lower than Grade: GB	Class GA
14	Resistance to staining	Not lower than Grade 3 for glazed tile	Class 5
15	Resistance to acid (in 3% HCl liquor four days)	Class GLB	Class GLA
16	Resistance to alkali (in 30g LKOH liquor four days)	Class GLB	Class GLA
17	Abrasion resistance floor tile 30x30 cm	PEI I-V	PEI I
18	Anti-slip degree floor tile 30x30 cm	R 9-12	R 9

nu pun in pericol viata, sanatatea, securitatea muncii si protectia mediului si sunt in conformitate cu normele in vigoare din punct de vedere al calitatii produsului.

