



# Zalakerámia

## Data sheet

Type of product:	glazed	ceramic tile	dry pressed
Norm:	EN 14411 Annex G E $\leq$ 0,5% Bla group		
Glaze:	glazed		
Surface:	matt		
Product line:	NORMAN		
Catalogue code:	<b>ZGD 61208</b>	6061-0037-4201	
Normal size:	59x59x0,85 cm		
	591x591 mm	Kaliber 1	
	592x592 mm	Kaliber 2	
	593x593 mm	Kaliber 3	
	594x594 mm	Kaliber 4	
	590x590 mm	Kaliber 0	
	589x589 mm	Kaliber 9	
	588x588 mm	Kaliber 8	
	587x587 mm	Kaliber 7	

<i>essential characteristics</i>	<i>inspection method</i>	<i>nominal value</i>	<i>Zalakerámia production</i>
length and width	ISO 10545-2	$\pm 0,6\%$	$\pm 0,3\%$
thickness	ISO 10545-2	$\pm 5\%$	$\pm 3,0\%$
rectangularity	ISO 10545-2	$\pm 0,5\%$	$\pm 0,3\%$
straightness of edges	ISO 10545-2	$\pm 0,5\%$	$\pm 0,25\%$
curvature of edges	ISO 10545-2	$\pm 0,5\%$	+ 0,3%
centre curvature	ISO 10545-2	$\pm 0,5\%$	+ 0,3%
water absorption	ISO 10545-3	E $\leq 0,5\%$	average 0,3%
bending strength N/mm <sup>2</sup>	ISO 10545-4	min. 35	average 36
thermal shock resistance	ISO 10545-9	required	as per norm
resistance against patch-makers	ISO 10545-14	min. 3. Sort.	as per norm
chemical resistance against household chemicals	ISO 10545-13	min. GB	as per norm
resistance against pool chemicals	ISO 10545-13	min. GB	as per norm
wear resistance	ISO 10545-7	indicated by manufacturer	PEI 4
frost resistance	ISO 10545-12	required	frost resistant
anti-slip property	DIN 51130/1991	not required as EU norm	NPD

Hereby we confirm, that above mentioned product complies with rules of EN 14411 norm.  
Tófej, 26. 09, 2022

Svajda-Nagy Tímea  
Svajda-Nagy Tímea  
Quality manager  
**ZALAKERÁMIA ZRT.**  
Minőségbiztosítás 1.  
8946 Tófej  
3