



Technical Characteristic KAI/KOS  
FISA TEHNICA

ODU  
16.07.05(7/0)

Model: "Stnline" na  
Internal code: 9919  
Type: Rectified Porcelain Tiles GL  
Group Bla, Nominal size 600 x1200x8.5 mm

Characteristics/Caracteristici Group Bla, Annex G	Tolerance EN 14411:2016, %	Tolerance EN14411:2016, mm	Measured in KAI laboratory/Masuratori in laborator Kai		Testing method/Metoda de lucru
			Caliber	Size	
1. Work size, mm (Length/width/Lungime /Latime)	+0.6/max+2mm	±2.00	8	598 x 1198	EN ISO 10545-2
2.Thickness/Grosimea, mm	+5/max±0.5mm	0.45	8.5 ±0.4mm		EN ISO 10545-2
3. Straightness of sides /Liniaritatea muchiei,mm	+0.5/max11.5mm	+1.50	±0.8mm		EN ISO 10545-2
4. Rectangularity/ Recfangularitate, mm	±0.5/max±2mm	2.00	±0.8mm		EN ISO 10545-2
5. Centre curvature/ Curbura centrala, mm	+0.5/max±2mm	±2.00	CC - 0.6 mm; CV + 1.5 mm		EN 150 10545-2
6. Edge curvature/ Curbura laterala, mm	±0.5/max±2mm	*2.00	CC - 0.6 mm; CV + 1.5		Eh ISO 10545-2
7. Warpage /Deformarea, mm	±0.5/max+2mm	+2.00	CC — 0.6 mm; CV + 1.5		EN 150 10545-2
8. Surface quality/ Calitatea suprafetei	*95% without defects	a95% without defects	Pass		EN ISO 10545-2
9.Water absorption/ Absorbția de apa, %	s0,5% Individual s0,6%	s0,5% Individual s0,6%	0.04 — 0.17 %		EN ISO 10545-3
10.Modulus of rupture /rezistența mecanică, N/mm²	>35N/mm² individual*32N/mm²	a35N/mm² individual*32N/mm²	*35N/mm²		EN ISO 10545-4
11. Breaking strength/ Forta de rupere, N	1300	1300	*1300		EN ISO 10545-4
12.Determination of surface abrasion for glazed tiles/Rezistența la abraziune	the class of abrasive resistance and the number of cycles are declared by producer	the class of abrasive resistance and the number of cycles are declared by producer	4/ 6000		EN ISO 10545-7
13.Crazing resistance, glazed tiles/Resistența la crapături pentru plăci glazurate	Pass according to EN ISO 10545-1	Pass according to EN ISO 10545-1	Resistant		EN ISO 10545-11
14.Resistance for household chemicals and swimming pool salts/ Rezistența la soluțiile de uz casnic și sărurile de piscină	Min class B	Min class B	GA		EN ISO 10545-13
15.Resistance to the low concentration acids and alkalis/Rezistența la acizi și baze de concentrație slabă	Declared value	Declared value	GLA		EN 150 10545-13

16. Resistance to the high concentration acids and alkalis/ Rezistentă la acizi și baze de concentrație mare	Declared value	Declared value	GHA	EN ISO 10545-13
17. Stain resistance/ Rezistentă la gătare	Min class 3	Min class 3	class 5	EN 150 10545-14
18. Frost resistance/ Rezistentă la îngheț	Pass according to EN ISO 10545-1	Pass according to EN ISO 10545-1	Resistant	EN ISO 10545-12
19. MOHS/ Rezistentă la zgăriere	Declared value	Declared value	9	EN 101:1991
20. Slipperiness/ Rezistentă la alunecare	Declared value	Declared value	PTV 36+ Dry PTV 36* Wet	BS 7976
21. Slipperiness/ Rezistentă la alunecare	Declared value	Declared value	NG	DIN 51130

Date: 27.06.2023

