



Product Data Sheet

Eruption S

January, 2025

Type of flooring	EN ISO 26986	Expanded (cushioned) polyvinyl chloride floor covering	
Class of use	ISO 10874 (EN 685)		
CE certification	EN 14041:2004/AC:2006	2701-0106-DoP-2024-01	
TECHNICAL CHARACTERISTICS AND PERFORMANCES			
 ISO 24346 (EN 428) Total thickness	2,70 mm	 ISO 24341 (EN 426) Roll lenght Roll width	30 m (15-30) 3;4 m
 ISO 24340 (EN 429) Wear layer tickness	0,15 mm	 ISO 24343-1 (EN 433) Residual indentation	≤ 0,35 mm
 ISO 23997 (EN 430) Weight per m²	1,46 kg/m ²	 Underfloor heating Suitable provided that the surface of the subfloor does not exceed 27°C	
 ISO 105 B02 Method 3 Light fastness	≥ 6	 EN 13893 Slip resistance	
 ISO 23999 (EN 434) Dimensional stability	Requirement by standard:< 0,4 % Tarkett result: ≤ 0,011 %	EN 12524 Thermal resistance	0,038 - 0,044 m ² /kW
 EN 13501-1 Fire classification	Bfl-s1		
Wear layer binder content ISO 11638 Type I			



2701-0106-DoP-2024-01



This product is 100% recyclable

