

Product sheet

Basic Information

Order Number
Type
Common Number





2309010030
UTP CAT5E PVC 2M
S9123



8595025385499

Measuring Unit
Packaging
Net Weight [kg]
Dimensions [mm]
Technical Support

KS
1 / - / - / 60
0.05
15 × 118 × 255
Petr Veselý, 581261172,
vesely@emos.cz



Basic Product Description

Unshielded patch cable of category CAT5E with moulded protection.

Technical Description

warranty period	5 years
product	cable with connectors
connectors	RJ45/RJ45
connector protection type	cast
type	UTP CAT 5E 2M
length	2 m
cable structure	stranded wires
category	5E
material of the inner conductor	copper clad Al (CCA)
AWG	26
inner conductor diameter	0.53 mm
wire insulation	HDPE
conductor insulation thickness	0.22 mm
strength member	Nylon 150D

Product sheet

cable sheath	PVC
jacket diameter	5 mm
jacket thickness	1.1 mm
sheath color	grey (RAL 7035)
marking of cable	UTP Cat5E PVC Patch cable
highest supported protocol	1000 Base-T (Gigabit Ethernet)
storage temperature	-20 °C to +60 °C
mounting temperature	+5 °C to +60 °C
maximum operating humidity	93 %
reaction to the fire	do not subject to CPR
dangerous substances	do not subject to CPR
number of wires	8
packaging	1 pc, PVC packet