

DECLARATION OF PERFORMANCE CURTA-105/30



Reference Number	DOP_AKD_CURTA 10530 06 / 22	
Unique Identification Code of the Product	MW-TSEN13162-T4-DS(70,-) -CS(10)20-TR5 -WS 1-WL(P)3-MU1 Thermal and sound insulation boards made of stone wool fibers in line with EN 13162:2012 +A1 : 2015	
Type, batch or serial number or any other element allowing identification of the construction product as required in Article 11 (4) of the CPR	Identification of the product (type, serial number tec) is available in the shipment documents	
Intended use or uses of the construction product in acc. with the applicable harmonized technical specification, as by the manufacturer	Thermal insulation of building equipment and industrial installations	
Name, registered trade name or registered trade mark and contact address as required by Article 11 (5) of the CPR	AKDAG GRANIT MER. VE MAD.SAN.TIC.A.S. Organize Sanayi Bolgesi 2. Yol. NO:3 ELAZIG www.akdagtasyunu.com e-mail: bilgi@akdagtasyunu.com	
Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified by Article 12 (2) of the CPR	Mr. Taha Yasin Akdağ , General Manager	
System or Systems Assessment and Verification of Constancy of Performance of the construction product as required by Annex V of the CPR	System 1	
In case of the Declaration of Performance concerning a construction product covered by a Harmonized standard	TZUS s.p NB 1020 performed Factory Production Control under system 1 + and issued certificate of Constancry of Performance: 1020-CPR-010045571 and protocol on product certification report no: 010-045570	

Performance		
Essential Characteristics	Performance	Technical Specification
Density, kg/m ³	105	EN 13162:2012+A1:2015
Length, mm	1200 (±3,5)	
Width, mm	600 (±2)	
Thickness, mm	30 (-3%/+5%)	
Fire classification	A1	
Compressive strength at 10% deformation, Kpa	≥ 20	
Tensile strength,Kpa	≥ 5	
Thermal resistance ,RD	0,86	
Thermal Conductivity at 10°C, W/(m*K), not more	0,035	
Water absorption, short-term, kg/m², not more	1	
Water absorption, long-term, kg/m², not more	3	
Water vapour diffusion resistance factor, μ	1	

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issue in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

General Manager

Taha Yasin Akdağ

AKAAC GRANIT NERMER VE MADEN SAN. IIC. A.S.
Openize Safayi Bolgesi 4 Yol No yo
lei - 0 424 256 54 33 Fax. 255 54 34 ELAZIG
Hazar V.D. 026 045 1072 Tic.Sic.No:10646

Elazig / TURKEY 01.06.2022