



Product Data Sheet Start

May, 2023

Type of flooring	EN ISO 26986	Expanded (cushioned) polyvinyl chloride floor covering
Class of use	ISO 10874 (EN 685)	
CE certification	EN 14041:2004/AC:2006	2701-0084-DoP-2021-11

TECHNICAL CHARACTERISTICS AND PERFORMANCES

	ISO 24346 (EN 428) Total tickness	2,00 mm		ISO 24341 (EN 426) Roll lenght Roll width	38m (15-38) 30m (15-30) 3m; 2; 4m
	ISO 24340 (EN 429) Wear layer tickness	0,13 mm		ISO 717/2 Impact sound absorption	17 dB
	ISO 23997 (EN 430) Weight per m ²	1,350 kg/m ²		ISO 24343-1 (EN 433) Residual indentation	≤ 0,35 mm
	ISO 105 B02 Method 3 Light fastness	≥ 6		Underfloor heating Suitable provided that the surface of the subfloor does not exceed 27°C	
	ISO 23999 (EN 434) Dimensional stability	Requirement by standard: < 0,4 % Tarkett result: ≤ 10,011 %		EN 13893 Slip resistance	
	EN 13501-1 Fire classification	Bfl-s1		EN 12524 Thermal resistance	0,02 - 0,03m ² /kW

Wear layer binder content ISO 11638 Type I



2701-0084-DoP-2021-11



This product is 100% recyclable

