Technical Data Sheet

Rust-Oleum Neon Paint (150ml Aerosol): Green (Matt), Pink (Matt) & Yellow (Matt)

A premium quality, fast drying acrylic spray paint for use on most indoor surfaces.

Preparation: Ensure surfaces to be painted are clean, dry and free from loose paint, rust, wax, oil and grease. Previously painted surfaces should be abraded to provide a key. Surfaces to be painted should be primed with Rust-Oleum Surface Primer in White. Cover surrounding areas to protect from spray mist.

Application: Shake can vigorously for 1 minute after mixing ball begins to rattle, continue to shake regularly during use. Hold can 30cm from surface and spray in a steady back and forth motion, slightly overlapping with each stroke. For best results whilst spraying keep the can the same distance from the surface and keep the can in motion. Apply several light coats a few minutes apart.

Cleaning: After use invert can and spray for 2-3 seconds to clear the spray nozzle.

Drying & Recoating: Touch dry in 15 minutes. Recoat after 20 minutes.

Coverage: A 150ml can covers approximately 0.75m² dependent upon surface profile / porosity.

Limitations: Interior use only, colour intensity will reduce if in strong sunlight for extended periods. Do not use on surfaces that regularly exceed temperatures over 80°C. Special precautions should be taken during the preparation of pre 1960's paint surfaces over wood and

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK. **Technical Services Department: 0191 410 6611**

E-mail: info@tor-coatings.com www.tor-coatings.com or www.rustoleumspraypaint.com

metal as they may contain harmful lead. When dry-sanding avoid dust inhalation by wearing a suitable protective face mask.

Shelf life: 3 years (unopened) from date of manufacture. (See base of can).

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.