

Technical Data Sheet

Honest General Trading SRL CIF: RO 6615609 Reg.Com: J40/25279/1994 Head Office: Agricultori 121 street, Sector 3, Bucharest www.honest.ro



Flush Valve

| HGT code | Name | Code | G[kg] | EAN Code | Packing | Description | |
|----------|--|--------------|-------|---------------|---------|---|------------|
| | | | N.W.* | | | Main Material | ABS and PP |
| 680022 | Mecanism Evacuare Vas WC / Actionare: Mecanica; D[inch]: 2; h[mm]: 250 | C2112M+P2404 | 0.386 | 5949094039211 | 1/15 | Gasket material | Rubber |
| 680023 | Mecanism Evacuare Vas WC / Actionare: Pneumatica; D[inch]: 2; h[mm]: 250 | C2312+P2304 | 0.373 | 5949094039228 | 1/15 | Finish button | Chromate |
| | | | | | | Button Color | Silver |
| | | | | | | - Warranty Certificate and instruction required | |
| | | | | | | 5 year warranty | |
| | | | | | | Individual packing Type | Carton box |
| | | | | | | - N.W.*=net weight. | |

-





| Descripti | on |
|------------|---|
| Dual Flu | sh Valve C2112M |
| 2 " outle | size, for 2-PC toilet |
| Adjustab | e overflow pipe: 20-28 cm |
| Installati | on height: 25 cm |
| With half | and full flush adjustment mechanism |
| P2404 Dı | al Push button Chrome plated surface, diameter 48 mm |
| Flushing | flow rate: 2.3L/S |
| Life span | 200,000 times for half flush,200,000 times for full flush |



| Description | | | | | |
|--|--------|--|--|--|--|
| Toilet tank Fittings, including, C2312+P2304Cable Flush Valve | | | | | |
| Patented construction control box to achieve stable performance under different cond | itions | | | | |
| Cable drive, maximum flexibility; | | | | | |
| Dual flushing, water saving | | | | | |
| Adjustable overflow pipe , 20 to 28 cm | | | | | |
| With round push button, for top push, 38 mm diameter | | | | | |
| 2" outlet size, for 2-PC toilet | | | | | |
| Flushing flow rate:2.1 L/s | | | | | |
| Dual flush, water saving | | | | | |
| Life Span: 200,000 times for half flush, 200,000 times for full flush | | | | | |



Logo EVO must be engraved here