

DECLARATION OF PERFORMANCE

NO:GP-30/60-01

30x60 Serie "Travertino Classic"

Identification of The Product	Dry-pressed ceramic porcelain tiles, Group Bla with low water absorption E _b ≤	
	0,5 %, sizes: 300x600x8.0 mm	
Intended Use(s)	Internal and external floor and wall	
	Dura-tiles BG JSK	
Name and Contact Address of the	Tsar Osvoboditel Str, 43-9900, Novi	
Manufacturer	Pazar- BULGARIA	
TO THE CONTRACTOR OF THE CONTRACTOR OF THE	Tel:+359 53722100, info@duratiles.bg	
Systems of Assessment	System 4	
Notified Laboratory and Nº of the test report with issue date.	Building Research Institute, Sofia-	
	Bulgaria	
	Test report# 646-3-200/09.10.2017	

According to the EU Regulation No: 305/2011 of the European Parliament and of The Council the products mentioned above confirm all the requirements of **EN 14411:2016** standard by these declared values:

Essential Characteristics	Declared Values	Harmonized Tech.Spec.
Reaction to fire	Class A1/FL	БДС EN 14411:2016
Release of Cadmium	NPD	
Release of Lead	NPD	
Breaking Strength, thickness ≥7.5mm	Min. 1300 N	
Breaking Strength, thickness < 7.5mm	Min. 700 N	
Slipperiness	R9	
PEI	4	
Tactility	NPD	
Bond Strength (cementations ad)	≥0.5 N/mm2	
Crazing Resistance	Resistant	
Thermal Shock Resistance	Resistant	
Freeze/Thaw Resistance	Resistant	

The performance of the product subject to this declaration is in conformity with the declared performance in the table above.

This declaration of performance is issued under the sole responsibility of Dura-tiles BG JSC.

