



Zalakerámia

Data sheet

| | | | |
|------------------|-----------------------------------|-----------------|-------------|
| Type of product: | glazed | ceramic tile | dry pressed |
| Norm: | EN 14411 Annex L E>10% BIII group | | |
| Glaze: | glazed | | |
| Surface: | glossy | | |
| Product line: | Carneval | negru structura | |
| Catalogue code: | ZBK 62010 | 2064-0132-3501 | |
| Normal size: | 20x60x1,0 cm | | |
| | 201x601 mm | Kaliber 1 | |
| | 200x600 mm | Kaliber 0 | |
| | 199x599 mm | Kaliber 9 | |
| | 199x598 mm | Kaliber 8 | |

| <i>essential characteristics</i> | <i>inspection method</i> | <i>nominal value</i> | <i>Zalakerámia production</i> |
|---|--------------------------|----------------------|-------------------------------|
| length and width | ISO 10545-2 | ± 0,5% | ± 0,3% |
| thickness | ISO 10545-2 | ± 10% | ± 3,0% |
| rectangularity | ISO 10545-2 | ± 0,5% | ± 0,3% |
| straightness of edges | ISO 10545-2 | ± 0,3% | ± 0,25% |
| curvature of edges | ISO 10545-2 | ± 0,5% | + 0,3% |
| centre curvature | ISO 10545-2 | ± 0,5% | + 0,3% |
| water absorption | ISO 10545-3 | E >10% | average 18% |
| bending strength N/mm ² | ISO 10545-4 | min. 12-15 | average 20 |
| thermal shock resistance | ISO 10545-9 | required | as per norm |
| chemical resistance against household chemicals | ISO 10545-13 | min. GB | as per norm |
| resistance against pool chemicals | ISO 10545-13 | min. GB | as per norm |
| wear resistance | ISO 10545-7 | not required | - |
| frost resistance | ISO 10545-12 | not required | - |

Hereby we confirm, that above mentioned product complies with rules of EN 14411 norm.

Tófej, 06.08. 2021.

ZALAKERÁMIA ZRT.