



<b>Type:</b>	<b>57642</b>	<b>Systems to charge:</b>	<b>Ni-MH</b>
Designation:.....	<b>Pocket charger</b>	Cell sizes:.....	AAA, AA
		Cell Configurations:.....	AAA, AA, 2/4 pcs.

<b>Dimensions:</b>	<b>Charger:</b>
Length:.....	130 ± 1 mm
Width:.....	51 ± 1 mm
Height:.....	82 ± 1 mm
Weight:.....	99 g

<b>Charging methods:</b>	<b>AC 220-240V 50-60Hz</b>	<b>Maintenance Charge:</b>
AA:.....	Current: 220-250 mA ± 20%	Current: 0mA
AAA:.....	Current: 120-140 mA ± 20%	Current: 0mA

<b>Housing:</b>	<b>Indications: LED display</b>
Housing Material:..... PC	AAA, AA, cell mix:..... LED solid on = charge
Casing color:..... black, grey	AAA, AA, cell mix:..... LED off = charge end
	AAA, AA, cell mix:..... LED flash= short circuit

<b>Protective Functions:</b>	<b>Power:</b>
Mechanical inverse-polarity protection	Primary:..... 100-240 VAC 50/60 Hz
	Secondary:..... 2.8V

<b>Cut off criteria:</b>	
Ni-MH standard cells:...	Timer: Backup timer 13hour

**No publication or circulation of data to third parties without consent of VARTA Consumer Batteries**