

Caracteristici tehnice radiatoare portprosop Quadro

Latime [mm]	Inaltime [mm]	Bare intermediare [buc]	Putere termica Δt 50 [w]	Grup bare intermediare [buc]	Diametrul tevilor [mm]
400	700	10	221	3+3+4	22
400	800	11	247	3+4+4	22
400	1000	14	313	3+3+4+4	22
400	1100	16	351	3+5+5+5	22
400	1200	18	390	3+5+5+5	22
400	1400	22	467	3+5+6+8	22
400	1500	23	494	3+5+7+8	22
400	1600	24	521	3+6+7+8	22
400	1800	26	584	3+7+7+9	22
500	700	10	260	3+3+4	22
500	800	11	291	3+4+4	22
500	1000	14	368	3+3+4+4	22
500	1100	16	414	3+5+5+5	22
500	1200	18	461	3+5+5+5	22
500	1400	22	554	3+5+6+8	22
500	1500	23	585	3+5+7+8	22
500	1600	24	615	3+6+7+8	22
500	1800	26	694	3+7+7+9	22
600	700	10	299	3+3+4	22
600	800	11	334	3+4+4	22
600	1000	14	423	3+3+4+4	22
600	1100	16	477	3+5+5+5	22
600	1200	18	532	3+5+5+5	22
600	1400	22	641	3+5+6+8	22
600	1500	23	675	3+5+7+8	22
600	1600	24	710	3+6+7+8	22
600	1800	26	804	3+7+7+9	22