

Declaration of performance
№ DPCTLWGL001KAIG

(UK)-Rev. №2

1) Unique identification code of the product-type;

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Dry-pressed ceramic tiles with low water absorption $E_b \leq 0.5\%$, glazed, for internal and external walls and floorings

2) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **external and internal surface finishes-floors, walls**

3) Name registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): **KAI Group: Khan Asparuh AD, Ispereh, 1 Ahinora Str., Phone: +35984312577, Fax: +35984313613; E-mail: info@kai.bg; Khan Omurtag AD, Shumen, Varnensko Shosse STR, Phone: +35954830487, Fax: +35954832692; E-mail: info@kai.bg**

4) Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): *not applicable*

5) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

6) In case of the declaration of performance concerning a construction product covered by a harmonized standard: Name and number of notified body: *not applicable*

7) Declared performance/s:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class A1fl/A1	EN 14411:2012
Release of dangerous substances: - cadmium - lead - other	NPD NPD NPD	
Breaking strength - thickness $\geq 7.5\text{mm}$ - thickness $< 7.5\text{mm}$	$\geq 1300\text{N}$ $\geq 700\text{N}$	
Durability for: - internal use - external use-freeze-thaw resistance	Pass Pass	
Bond strength/adhesion - cementitious adhesive - dispersion adhesive - reactive resin adhesive - mortar	$\geq 0.5\text{ N/mm}^2$ $\geq 1.0\text{ N/mm}^2$ $\geq 2.0\text{ N/mm}^2$ NPD	
Thermal Shock Resistance	Pass	
Tactility	NPD	
Slipperiness	See the table	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ispereh, 01.11.2020.

Plamen Pashev

Operations Director



Declaration of performance
Nº DPCTLWGL002KAIG

(UK)-Rev. Nº2

1) Unique identification code of the product-type;

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Dry-pressed ceramic tiles with low water absorption $E_b \leq 0.5\%$, unglazed, for internal and external walls and floorings

2) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **external and internal surface finishes-floors, walls**

3) Name registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): **KAI Group: Khan Asparuh AD, Ispernih, 1 Ahinora Str., Phone: +35984312577, Fax: +35984313613; E-mail: info@kai.bg**

4) Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): *not applicable*

5) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

6) In case of the declaration of performance concerning a construction product covered by a harmonized standard: Name and number of notified body: *not applicable*

7) Declared performance/s:

Essential Characteristics	Performance	Harmonized technical Specification
Reaction to fire	Class A1fl/A1	EN 14411:2012
Release of dangerous substances: - cadmium - lead - other	<0.01mg/dm ² <0.1mg/dm ² NPD	
Breaking strength - thickness ≥ 7.5mm - thickness < 7.5mm	≥ 1300N ≥ 700N	
Durability for: - internal use - external use-freeze-thaw resistance	Pass Pass	
Bond strength/adhesion - cementitious adhesive - dispersion adhesive - reactive resin adhesive - mortar	≥ 0.5 N/mm ² ≥ 1.0 N/mm ² ≥ 2.0 N/mm ² NPD	
Tactility	NPD	
Slipperiness	See the table	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ispernih, 01.11.2020.

Plamen Pashev

Operations Director



Declaration of performance
№ DPCTF003KAIG

(UK)-Rev. №2

- 1) Unique identification code of the product-type;
Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
Dry-pressed ceramic tiles with water absorption $3% < E_b \leq 6%$, for internal floorings
- 2) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **internal surface finishes-floors**
- 3) Name registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): **KAI Group: Khan Asparuh AD, Isperih, 1 Ahinora Str., Phone: +35984312577, Fax: +35984313613; E-mail: info@kai.bg; Khan Omurtag AD, Shumen, Varnensko Shosse STR, Phone: +35954830487, Fax: +35954832692; E-mail: info@kai.bg**
- 4) Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): *not applicable*
- 5) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**
- 6) In case of the declaration of performance concerning a construction product covered by a harmonized standard: Name and number of notified body: *not applicable*
- 7) Declared performance/s:

Essential Characteristics	Performance	Harmonized technical Specification
Reaction to fire	Class A1fl/A1	EN 14411:2012
Release of dangerous substances: - cadmium - lead - other	NPD NPD NPD	
Breaking strength - thickness $\geq 7.5\text{mm}$ - thickness $< 7.5\text{mm}$	$\geq 1000N$ $\geq 600N$	
Durability for: - internal use	Pass	
Thermal Shock Resistance	Pass	
Tactility	NPD	
Slipperiness	See table	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Isperih, 01.11.2020.

Plamen Pashev
Operations Director



Declaration of Performance
№ DPCTW004KAIG

(UK)-Rev. №2

- 1) Unique identification code of the product-type;
Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
Dry-pressed ceramic tiles with water absorption $E_b > 10\%$, for internal walls
- 2) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **internal surface finishes-walls**
- 3) Name registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): **KAI Group: Khan Asparuh AD, Isperih, 1 Ahinora Str., Phone: +35984312577, Fax: +35984313613; E-mail: info@kai.bg; Khan Omurtag AD, Shumen, Varnensko Shosse STR, Phone: +35954830487, Fax: +35954832692; E-mail: info@kai.bg**
- 4) Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): *not applicable*
- 5) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 3**
- 6) In case of the declaration of performance concerning a construction product covered by a harmonized standard: Name and number of notified body: Lucideon NB1289 performed a test to determine the emission of hazardous substances according to System 3 and issued Product Conformity Certifications PC 024; PC 047, containing the protocol numbers of the type testing.
- 7) Declared performance/s:

Essential Characteristic	Performance	Harmonized technical Specification
Reaction to fire	Class A1	EN 14411:2012
Release of dangerous substances: - cadmium - lead - other	<0,01 mg/dm ² <0,1 mg/dm ² NPD	
Durability for: - internal use	Pass	
Bond strength/adhesion - cementitious adhesive - dispersion adhesive - reactive resin adhesive - mortar	≥0.5 N/mm ² ≥1.0 N/mm ² ≥2.0 N/mm ² NPD	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Isperih, 01.11.2020.

Plamen Pashev
Operations Director



Declaration of performance
№ DPCTFW009KAIG

(UK)-Rev. №2

- 1) Unique identification code of the product-type;
 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
Dry-pressed ceramic tiles with water absorption 6% $E_b \leq 10$, for internal walls and floorings
- 2) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **internal surface finishes-floors, walls**
- 3) Name registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): **KAI Group: Khan Asparuh AD, Isperih, 1 Ahinora Str., Phone: +35984312577, Fax: +35984313613; E-mail: info@kai.bg; Khan Omurtag AD, Shumen, Varnensko Shosse STR, Phone: +35954830487, Fax: +35954832692; E-mail: info@kai.bg**
- 4) Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): *not applicable*
- 5) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**
- 6) In case of the declaration of performance concerning a construction product covered by a harmonized standard: Name and number of notified body: *not applicable*
- 7) Declared performance/s:

Essential Characteristics	Performance	Harmonized technical Specification
Reaction to fire	Class A1fl	EN 14411:2012
Release of dangerous substances: - cadmium - lead - other	NPD NPD NPD	
Breaking strength - thickness $\geq 7.5\text{mm}$ - thickness $< 7.5\text{mm}$	$\geq 800\text{N}$ $\geq 500\text{N}$	
Durability for: - internal use	Pass	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Isperih, 01.11.2020.

Plamen Pashev
Operations Director



Declaration of performance
№ DPCTLMWGL011KAIG

(UK)-Rev. №2

- 1) Unique identification code of the product-type;
 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
- Dry-pressed ceramic tiles with water absorption $0,5\% < E_b \leq 3\%$, for internal and external walls and floorings**
- 2) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **external and internal surface finishes-floors, walls**
- 3) Name registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): **KAI Group; Khan Asparuh AD, Ispernih, 1 Ahinora Str., Phone: +35984312577, Fax: +35984313613; E-mail: info@kai.bg; Khan Omurtag AD, Shumen, Varnensko Shosse STR, Phone: +35954830487, Fax: +35954832692; E-mail: info@kai.bg**
- 4) Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): *not applicable*
- 5) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**
- 6) In case of the declaration of performance concerning a construction product covered by a harmonized standard: Name and number of notified body: *not applicable*
- 7) Declared performance/s:

Essential Characteristics	Performance	Harmonized technical Specification
Reaction to fire	Class A1fl/A1	EN 14411:2012
Release of dangerous substances: - cadmium - lead - other	NPD NPD NPD	
Breaking strength - thickness $\geq 7.5\text{mm}$ - thickness $< 7.5\text{mm}$	$\geq 1100\text{N}$ $\geq 700\text{N}$	
Durability for: - internal use - external use-freeze-thaw resistance	Pass Pass	
Bond strength/adhesion - cementitious adhesive - dispersion adhesive - reactive resin adhesive - mortar	$\geq 0.5 \text{ N/mm}^2$ $\geq 1.0 \text{ N/mm}^2$ $\geq 2.0 \text{ N/mm}^2$ NPD	
Thermal Shock Resistance	Pass	
Tactility	NPD	
Slipperiness	NPD	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ispernih, 01.11.2020.

Plamen Pashev
Operations Director

