Technical Data Sheet

Rust-Oleum Flexible Fabric Paint (150ml Aerosol) Black, Silver (Metallic) & Gold (Metallic)

A fast drying, colouring dye for leather, vinyl and most fabrics.

Preparation: Ensure surfaces to be painted are clean, dry and free from wax, oil and grease. Cover surrounding areas to protect from spray mist. Test for suitability on an inconspicuous area before using on new applications.

Application: Shake can thoroughly before and during use. Hold can 25-30cm from surface and spray with light, even strokes in a steady back and forth motion, slightly overlapping with each stroke. For best results whilst spraying keep the can the same distance from the surface and keep the can in motion.

Cleaning: To clear spray for future use, turn can upside down and spray until clear gas is emitted.

Drying & Recoating: Touch dry in 15 minutes. Recoat where required after 20 minutes. Drying times are based on warm (15°C), dry application conditions with good ventilation. Lower temperatures and higher humidity will prolong the drying times.

Coverage: A 150ml can covers approximately 0.75m² dependent upon surface profile / porosity.

Limitations: Do not use on surfaces that regularly exceed temperatures over 80°C.

Shelf life: 3 years (unopened) from date of manufacture. (See base of can).

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK. **Technical Services Department: 0191 410 6611**

E-mail: info@tor-coatings.com www.tor-coatings.com or www.rustoleumspraypaint.com

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.