

Laminate floorcoverings
Commercial 31
FLOORPAN PINK "Wenge classic" 1380x193x8 class 31 TC 5536-003-65501405-2016
1. Normative reference: TC 5536-003-65501405-2016

2. Usage area: For floors in domestic and public buildings.

3. Main parameters:

Index		Value	
Density, kg/m ³		906	
Thickness, mm		8	
Width, mm		193	
Length, mm		1380	
Permitted thickness deviation, mm		± 0,2	
Permitted width deviation, mm		± 0,2	
Permitted length deviation, mm		± 0,5	
Squareness deviation, mm, not more		0,20	
Straightness deviation, mm/m, not more		0,30	
Flatness deviation, %, not more	width	concave	0,15
		convex	0,2
	length	concave	0,5
		convex	1,0
Width and length deviation after after relative humidity change, mm, not more.		0,9	
Surface soundness, N/mm ² , not less.		1,0	
Hydro thermal stability of the surface		Slight loss of glow is permitted.	
Thermal stability of the surface		Appearance changes are not allowed, except for slight loss of glow and colour.	
Resistance to abrasion quantity of spins, not less		2500	
Resistance class		AC 3	
Impact resistance drop height – 1400 mm, not less		Cracks and stratifications at ball drop area are not allowed. Imprint diameter not more than 9 mm.	
Resistance class		IC 1	
Resistance to staining		Appearance changes are not allowed.	
Resistance to cigarette burns, grade		4	
Thickness swelling, % not more		18,0	

Batch No. _____

Production date _____

Delivery date _____

Quality control and certification department chief _____

L.S.
Ms. Klimenko S.