

# Technical Data Sheet

Rust-Oleum Glow In The Dark (400ml Aerosol): Bright Green

---

**A special paint for use on plastic, wood, and metal which glows after exposure to light. Use on light switches, ceilings and walls, lamp bases, door frames and more.**

## Interior or Exterior Use

**Preparation:** For best results apply over a white or light coloured background. Ensure surfaces to be painted are free from loose paint, rust, wax, oil and grease. Previously painted surfaces should be abraded to provide a key. Cover surrounding areas to protect from over spray.

**Application:** Shake can vigorously for 1 minute after mixing ball begins to rattle, continue to shake regularly during use. Hold can 30cm from surface and spray in a steady back and forth motion, slightly overlapping with each stroke. For best results whilst spraying keep the can the same distance from the surface and keep the can in motion. Apply several light coats a few minutes apart.

**Cleaning:** To clear spray for future use, turn can upside down and spray until clear gas is emitted.

**Drying & Recoating:** Touch dry in 20 minutes. Hard dry in 24 hours. Recoating - Additional coats can be applied after 1 hour. Drying times are based on warm (15°C), dry application conditions with good ventilation. Lower temperatures and higher humidity will prolong the drying times. 1-2 coats required.

**Coverage:** A 400ml can covers approximately 2.5m<sup>2</sup> dependent upon surface profile / porosity.

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK.

**Technical Services Department: 0191 410 6611**

E-mail: [info@tor-coatings.com](mailto:info@tor-coatings.com) [www.tor-coatings.com](http://www.tor-coatings.com) or [www.rustoleumspraypaint.com](http://www.rustoleumspraypaint.com)

**Limitations:** Apply only when temperature is between 10-32°C and relative humidity below 85%. Special precautions should be taken during the surface preparation of pre 1960's paint surfaces over wood and metal as they may contain harmful lead. When dry-sanding avoid dust inhalation by wearing a suitable protective face mask. A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. For further information please contact our Technical Services Department.

**Shelf Life:** 3 years (unopened) from date of manufacture. (See base of can).

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.