

PRODUCT DATASHEET

LED BULB FA-8W/C37/865L E27

Consumer Products LED Bulb C37 | LED lamps, classic bulb shape



- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires



PRODUCT BENEFITS

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time
- Poly covered aluminium housing with better heating diffusion
- Built-in constant current driver better stability of usage

PRODUCT FEATURES

- LED alternative to conventional lamps
- Mercury-free lamps




TECHNICAL DATA


Electrical data

| Rated wattage | 8.00 W |
|--|------------|
| Nominal wattage | 8.00 W |
| Nominal voltage | 185-240VAC |
| Operating frequency | 5060 Hz |
| Power factor λ | > 0.50 |
| Claimed equiv. conventional lamp power | 70 W |

Photometrical data

| Rated luminous flux | 720 lm |
|--------------------------------------|------------|
| Light color (designation) | Cool White |
| Color temperature | 6500 K |
| Luminous flux | 720 lm |
| Color rendering index Ra | ≥80 |
| Standard deviation of color matching | ≤6 sdcm |
| Nominal luminous flux | 720 lm |
| Rated color temperature | 6500 K |
| Color rendering index Ra | ≥80 |





Light technical data

| Starting time | < 0.5 s |
|---------------|---------|
| Beam Angle | 260° |

Dimensions & weight



| Overall length | 110.0 mm |
|----------------|----------|
| Diameter | 37.0 mm |
| Outer bulb | C37 |
| Length | 110.0 mm |

Lifespan

| Nominal lamp life time | 25000 h |
|----------------------------|---------|
| Rated lamp life time | 25000 h |
| Number of switching cycles | 15000 |
| Warranty | 2 years |

Capabilities

Temperatures & operating conditions

| Ambient temperature range | -20+40 °C |
|--------------------------------------|-----------|
| Maximum temperature at tc test point | 98 °C |

Additional product data

| Base (standard designation) | E27 | |
|-----------------------------|--|--|
| Mercury-free | Yes | |
| Design / version | frosted | |
| Driver type | IC | |
| Product remark | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value | |
| Mercury content | 0.0 mg | |
| Standards | CE/CCC | |

Order code/Name

Order code/Name

FA2558 LED BULB FA-8W/C37/865L E27

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|--------------|------------------------------|--------------------------------------|--------------|----------------------|
| FA2558 | Folding carton box 1 | 37 mm x 37 mm x 110 mm | 35.50 g | 0.15 dm ³ |
| FA2558 | Shipping carton box 100 | 400 mm x 205 mm x 240 mm | 3700.00 g | 0.020 m ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping

REFERENCES / LINKS

For further products and actual information concerning LED lamps see www.fucida.eu

For Guarantee see www.fucida.eu

DISCLAIMER

Subject to change without notice. Errors and omission excepted.

PRODUCT DATASHEET