

LLC "KASTAMONU INTEGRATED WOOD INDUSTRY"		PRODUCT		YEL32T-FP20 8X193X1380
Control settings	Standard	Measurement unit	Tolerance Range	
Thickness	EN 13329	mm.	t max.- t min. ≤ 0,5	
Density	EN 323	kg/m ³	880 ± 10	
Width	EN 13329	mm.	w max.- w min. ≤ 0,2	
Length	EN 13329	mm.	Δl ≤ 0,5	
Rectangularity	EN 13329	mm.	Max. 0,2	
Straightness	EN 13329	mm.	≤ 0,414 mm	
Width flatness	convexity, not more than	EN 13329	mm.	≤ 0,386 mm
	concavity, not more than	EN 13329	mm.	≤ 0,289 mm
Length flatness	convexity, not more than	EN 13329	mm.	≤ 13,80 mm
	concavity, not more than	EN 13329	mm.	≤ 6,90 mm
Resistance to abrasion	EN 13329	turnovers	≥ 4000	
Abrasion class	EN 13329	class	≥ AC4	
Impact resistance	EN 13329	class	≥ IC2	
Resistance to staining	EN 14323	score	not less than 5	
Resistance to a smoldering cigarette	EN 14323	score	not less than 4	
Thickness swelling	EN 13329	%	≤ 18	

Chief of department quality and certification



/Svetlana Klymenko/