	Tehničke karakteristike gotove robe MAŠINSKO TKANI TERIH ADRIA ED-03-00-01-047	Izdanje/ Версия/Edition 1 12.11.2019.	Strana/ Страница/ Page 1/3
		Revizija/ Ревизия/ Revision	



društvo sa ograničenom odgovornošću
21400 Bačka Palanka, Industrijska zona 14, Srbija

Общество с ограниченной ответственностью
21400 БАЧКА ПАЛАНКА, Индустриальная зона 14, СЕРБИЯ

Limited Liability Company
21400 Backa Palanka, Industrijska zona 14, Serbia


ED-03-00-01-047

Tehničke karakteristike gotove robe – MAŠINSKO TKANI TERIH ADRIA


Технические характеристики готовой продукции- Машино-тканые ковры – ADRIA


Technical characteristics of finished products- Machine woven rug ADRIA

Izradio/Создал/Created:	Odobrio/Утвердил/Approved by:	Pregledao i overio/Проверено/ Reviewed and verified by:
Menadžer razvoja, istraživanja i industrijalizacije / Менеджер по развитию, исследованию и индустриализации / R&D and industrialization Manager Lešić Vesna	Direktor razvoja, istraživanja dizajna i inovacija iz oblasti konstrukcije površine proizvoda/ Директор по развитию, исследованию, дизайну и инновациям на поверхности пола /R&D, design and floor surface innovation director Martinović Dragana	Predstavnik rukovodstva za IMS Tarkett doo/ Представитель руководства для ИСУ Tarkett doo /Representative of the management for IMS Tarkett doo

	Tehničke karakteristike gotove robe MAŠINSKO TKANI TEPIH ADRIA ED-03-00-01-047	Izdanje/ Версия/Edition 1 12.11.2019.	Strana/ Страница/ Page 2/3
		Revizija/ Ревизия/ Revision	

KOMERCIJALNI NAZIV PROIZVODA/ Торговое название продукта/ Commercial product name Denumire	ADRIA			
Tehničke karakteristike / Технические характеристики/ Technical characteristics Characteristici tehnice	Deklarisana vrednost/ Valori declare Declared value	Odstupanja/ Отклонения/ Tolerante ISO 14215	Jednica mere/ Единица измерения Unitate masura	Metoda ispitivanja/ Метод испытания/ Metoda test
Kvalitet / Тип качества / Quality type Calitate	Flat weave, 1/2V			ISO 2424
Broj sistema efektne osnove / Кол-во цветов / Number of chores	2		ch	
Gustina tkanja / Плотность тканья / Weave density Densitate	32 X 32		On 10 cm	ISO1763
Broj čvorova / Количество узлов / Number of knots Numar noduri	102.400	± 10%	Їв/шт./No./ m2	ISO 1763
Broj tačaka / Количество точек / Number of points Numar puncte			Їв/шт./No./ m2	ISO 1763
Visina flora / Pile height /Inaltime		± 10%	mm	ISO 2549
Укупна debljina poda / Общая Высота покрытия / Total thickness Grosime totala	4	± 10%	mm	ISO 1765
Sirovinski sastav flora / Сырьевой состав ворса / Pile raw material / Material	100% PP BCF		%	ISO 1833
Sirovinski sastav potke / Сырьевой состав утка / Weft raw material batatura	100% PP tape		%	ISO 1833
Sirovinski sastav vezivne osnove / Сырьевой состав связывающей основы / Chain warp raw material / Urzeala	100% PES		%	ISO 1833
Sirovinski sastav popunjavajuće osnove / Сырьевой состав пополюняющей основы / Stuffer raw material / Umplutura	85% PES 15% Cotton		%	ISO 1833
Vezivno sredstvo / Связывающее средство / Finishing agent for backcoating/ finisaj	100% Latex		%	Defined by Tarkett
Masa flora / Pile weight/ Greutate fir	660	± 10%	g/m2	ISO 8543
Masa potke / Weft weight / greutate batatura	370		g/m2	ISO 8543
Masa vezivne osnove / Вес связывающей основы / Chain warp weight greutate urzeala	70		g/m2	ISO 8543
Masa popunjavajuće osnove / Stuffer weight greutate umplutura	55		g/m2	ISO 8543
Masa vezivnog sredstva / Finishing agent for backcoating weight/ greutate agent finisaj	95		g/m2	Defined by Tarkett
Укупна masa//Total weight/ greutate totala	1.250	± 10%	g/m2	ISO 8543

	Tehničke karakteristike gotove robe MAŠINSKO TKANI TEPIH ADRIA ED-03-00-01-047	Izdanje/ Версия/Edition 1 12.11.2019.	Strana/ Страница/ Page 3/3
		Revizija/ Ревизия/ Revision	

Dozvoljeno odstupanje od deklariranih dimenzija tepiha: $\pm 3\%$ za širine i dužine do 100 cm $\pm 2\%$ za širine i dužine preko 100 cm	Dozvoljeno odstupanje od deklariranih dimenzija staza: $\pm 3\%$ za širine do 100 cm $\pm 2\%$ za širine preko 100 cm Dužine rolne staza: min 10 m Dozvoljeno odstupanje dužine staze u rolni 0.2%
Odstupanje visine flora i mase tepiha u plusu nisu ograničena.	
Toleranta dimensionalna $\pm 2\%$ pentru dimensiuni sub 100 cm $\pm 2\%$ pentru dimensiuni peste 100 cm	Toleranta dimensionalna traverse: $\pm 2\%$ pentru latimi sub 100 cm $\pm 2\%$ pentru latimi peste 100 cm lungime: min 10 m toleranta admisa pentru lungimea rolei: 0,2%
Toleranta in inaltime si greutate fir in plus - nelimitat	
Tolerance in defined rug size: $\pm 3\%$ for rugs widths and lengths by 100 cm $\pm 2\%$ for rugs widths and lengths over 100 cm	Tolerance in defined runner size: $\pm 3\%$ for runners width by 100 cm $\pm 2\%$ for runners width over 100 cm Length of the runner roll: min 10 m Tolerance allowed in the length of the runner roll: 0.2 %
Tolerance in pile height and carpet mass in plus is not limited.	
	

- Tarkett reserves the right to change technical specifications of products in accordance with standard EN 1307.
- Tarkett оставляет за собой право изменять технические характеристики в соответствии со стандартом EN 1307.
- Tarkett zadržava pravo da izmeni tehničke karakteristike proizvoda u skladu sa standardom EN 1307.