



Type Designation	4103
Designation IEC	LR03
System	Zn-MnO ₂ (Alkaline)
Shelf Life (Coding)*	10 years
Nominal Voltage [V]	1.5
Typical Capacity C [mAh]	1230 (discharge with high-resistance)
Permissible Temperature Range	- 10 °C ... 50 °C
Weight, approx. [g]	11,3
Volume [ccm]	3.5

Dimensions [mm]	min:	max:
∅	9.5	10.5
A	-	44.5
B	43.3	-
C	4.3	-
E	-	0.5
F	-	3.8
G	0.8	-



Typical Capacities (at 20°C):

Discharge Type	Load	End Voltage[V]	0.9
1H/12H, 7D/W Digital audio	50 mA	Time [h]	22,8
		Capacity [mAh]	1142
		Energy [mWh]	1417
Discharge Type	Load	End Voltage[V]	1.0
15S/M, 8H/D, 7D/W Remote control	24 Ω	Time [h]	20,9
		Capacity [mAh]	1100
		Energy [mWh]	1395
Discharge Type	Load	End Voltage[V]	0.9
4M/H, 8H/D, 7D/W Portable lighting	5,1 Ω	Time [min]	258
		Capacity [mAh]	985
		Energy [mWh]	1160

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

* In consideration of typical loss of capacity at storage and application.