



Ventil Compact tip 22

PURMO CV 22



COMENZII : CV22XXXXYYY

EXEMPLU : CV226001200

abreviere denumire

tip

înălțime

lungime

lungime [mm]	parametri $t_2 / t_1 / t_3$	înălțime [mm]					
		200	300	450	500	600	900
400	75/65/20 °C		384	539	588	684	955
	70/55/20 °C		308	430	469	545	759
500	75/65/20 °C		481	674	735	855	1 194
	70/55/20 °C		385	538	587	681	949
600	75/65/20 °C	413	577	808	882	1 025	1 433
	70/55/20 °C	331	462	646	704	817	1 138
700	75/65/20 °C	482	673	943	1 029	1 196	1 672
	70/55/20 °C	386	539	753	822	954	1 328
800	75/65/20 °C	551	769	1 078	1 176	1 367	1 910
	70/55/20 °C	442	616	861	939	1 090	1 518
900	75/65/20 °C	620	865	1 212	1 323	1 538	2 149
	70/55/20 °C	497	693	969	1 056	1 226	1 707
1000	75/65/20 °C	689	961	1 347	1 470	1 709	2 388
	70/55/20 °C	552	770	1 076	1 174	1 362	1 897
1100	75/65/20 °C	758	1 057	1 482	1 617	1 880	2 627
	70/55/20 °C	607	846	1 184	1 291	1 499	2 087
1200	75/65/20 °C	827	1 153	1 616	1 764	2 051	2 866
	70/55/20 °C	662	923	1 291	1 408	1 635	2 277
1400	75/65/20 °C	965	1 345	1 886	2 058	2 393	3 343
	70/55/20 °C	773	1 077	1 507	1 643	1 907	2 656
1600	75/65/20 °C	1102	1 538	2 155	2 352	2 734	3 821
	70/55/20 °C	883	1 231	1 722	1 878	2 180	3 035
1800	75/65/20 °C	1240	1 730	2 425	2 646	3 076	4 298
	70/55/20 °C	993	1 385	1 937	2 112	2 452	3 415
2000	75/65/20 °C	1378	1 922	2 694	2 940	3 418	4 776
	70/55/20 °C	1104	1 539	2 152	2 347	2 725	3 794
2300	75/65/20 °C	1585	2 210	3 098	3 381	3 931	5 492
	70/55/20 °C	1269	1 770	2 475	2 699	3 133	4 363
2600	75/65/20 °C	1791	2 499	3 502	3 822	4 443	6 209
	70/55/20 °C	1435	2 001	2 798	3 051	3 542	4 932
3000	75/65/20 °C	2067	2 883	4 041	4 410	5 127	7 164
	70/55/20 °C	1656	2 309	3 229	3 521	4 087	5 691

Puterea termică a radiatoarelor (W) în conformitate cu EN 442 pentru parametrii 75/65/20 °C și 70/55/20 °C.

[W/m] 90/70/20 °C coeficient n	868 1,3077	1211 1,3094	1701 1,3226	1857 1,3270	2163 1,3358	3033 1,3561
-----------------------------------	---------------	----------------	----------------	----------------	----------------	----------------

radiator la comandă