

Valena™ Life

switches with cover plate



7 521 01 + 7 540 31
(White/chrome)



7 522 06 + 7 541 11
(Royal Ivory)



7 521 65 + 7 541 21
(Link)



7 521 10 + 7 540 71
(Terracotta)



7 521 08 + 7 540 91
(Adria)

Valena In'Matic mechanisms supplied with cover plates and support frames. To be equipped with plates.
Supplied with mounted dust protection transparent shield.
After clipping in the rocker, all LED lamps light up blue.
Flowpack packaging: robust protection to ensure optimum operation.

Pack Cat.Nos Switches 10 AX - 250 V~

Pack	Cat.Nos	Switches 10 AX - 250 V~
		One-way switches Automatic terminals
15	7 521 01	White
15	7 522 01	Ivory
15	7 523 01	Aluminium
		Two-way switches Automatic terminals
15	7 521 06	White
15	7 522 06	Ivory
15	7 523 06	Aluminium
		Energy saving switches Automatic terminals Installed and works like a conventional switch/2-way switch. But in addition, it switches off automatically after 10 minutes if no movement is detected by the built-in IR detector cell. Detection field 120°. Detection range 8 m Compatible with any lamp - 12-150 W: incandescent and 230 V halogen - 12-150 VA: lamps with ferromagnetic or electronic ballast - 8-30 W (or 650 mA): LED and CFL All types of lamp can be mixed on the same circuit. Ideal for rooms where the light may be left switched on needlessly (child's bedroom, box room)
1	7 521 65	White
1	7 522 65	Ivory
1	7 523 65	Aluminium
		Intermediate switches Screw terminals
5	7 521 07	White
5	7 522 07	Ivory
5	7 523 07	Aluminium
		Illuminated one-way switch Equipped with low consumption LED 0.15 mA (Cat.No 0 676 84)
5	7 521 10	White
5	7 522 10	Ivory
5	7 523 10	Aluminium

Pack Cat.Nos Switches 10 AX - 250 V~ (continued)

Pack	Cat.Nos	Switches 10 AX - 250 V~ (continued)
		One-way indicator switches Automatic terminals Equipped with 3 mA low consumption LED (Cat.No 6 650 91)
5	7 521 04	White
5	7 522 04	Ivory
5	7 523 04	Aluminium
		Illuminated two-way switches Automatic terminals Equipped with 0.15 mA low consumption LED (Cat.No 0 676 86)
5	7 521 26	White
5	7 522 26	Ivory
5	7 523 26	Aluminium
		Illuminated intermediate switches Screw terminals Equipped with 0.15 mA low consumption LED (Cat.No 6 650 90)
5	7 521 48	White
5	7 522 48	Ivory
5	7 523 48	Aluminium
		2-gang one-way switches Automatic terminals
15	7 521 05	White
15	7 522 05	Ivory
15	7 523 05	Aluminium
		2-gang two-way switches Automatic terminals
15	7 521 08	White
15	7 522 08	Ivory
15	7 523 08	Aluminium