

COMMAND - SYSTEM BLACK

COMMAND DEVICES



GW 21 571

ONE-WAY SWITCHES - 250V AC

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 21 571	1P - 16AX	Neutral		200 W	1	80/320
GW 21 572	1P - 16 AX backlit	With replaceable neutral lens		200 W	1	30/60
GW 21 583	1P - 16AX illuminable	With replaceable neutral lens		200 W	1	30/60
GW 21 503	2P - 16 AX	Neutral	0/1	200 W	1	30/60
GW 21 504	2P - 16 AX backlit	With replaceable neutral lens		200 W	1	30/60
GW 21 584	2P - 16AX illuminable	With replaceable neutral lens		200 W	1	30/60
GW 21 005	2P - 10AX	With key	0/1	100 W	1	15/30

CHARACTERISTICS: the illuminable articles use miniature lamp units, not included.

ACCESSORIES SUPPLIED: GW21572, GW21504 - red fluorescent 230Vac (0.4W) signalling unit. GW21005 supplied with 2 keys. The key can be extracted in both positions. Spare keys: GW20901.



GW 21 585

ONE-WAY SWITCH 2P FOR HEAVY-DUTY INSTALLATIONS - 25A - 250V AC

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 21 585	25A	Neutral	0/1	250 W	1	15/30

CHARACTERISTICS: suitable for particular heavy-duty loads (e.g. set of fluorescent lamp) or high consumption devices (ovens, air-conditioners, boilers, etc.).



GW 21 576

TWO-WAY SWITCHES 1P - 250V AC

Code	Description	Button key	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 21 576	1P - 16AX	Neutral	200 W	1	80/320
GW 21 577	1P - 16 AX backlit	With replaceable neutral lens	200 W	1	30/60
GW 21 588	1P - 16AX illuminable	With replaceable neutral lens	200 W	1	30/60
GW 21 008	1P - 10AX	With key	100 W	1	15/30

CHARACTERISTICS: the illuminable articles use miniature lamp units, not included.

ACCESSORIES SUPPLIED: GW21577 - red fluorescent 230Vac (0.4W) signalling unit. GW21008 supplied with 2 keys. The key can be extracted in both positions. Spare keys: GW20901.



GW 21 579

INTERMEDIATE SWITCHES 1P - 250V AC

Code	Description	Button key	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 21 579	1P - 16AX	Neutral	200 W	1	30/60



GW 21 559

THREE-WAY SWITCH 1P - 250V AC

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 21 559	1P - 10AX	Neutral	UP - DOWN	100 W	1	30/60
GW 21 528	1P - 10AX	With replaceable neutral lens		100 W	1	30/60

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF).

GW21528 - not-illuminated product; equipped with neutral lens.

APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal), 2-user selective control.



GW 21 510

PUSH-BUTTONS - 250V AC

Code	Description	Button key	Symbol	No. SYSTEM modules	Pack Carton
GW 21 510	1P NO - 10A	Neutral		1	80/160
GW 21 511	1P NO - 10A	With symbol	Key	1	15/30
GW 21 512	1P NO - 10A	With symbol	Bell	1	15/30
GW 21 513	1P NO - 10A	With symbol	Light	1	15/30
GW 21 514	1P NO - 10A	With symbol	Stairs	1	15/30
GW 21 515	1P NO - 10 A backlit	With replaceable neutral lens		1	30/60
GW 21 516	1P NO - 10 A backlit	With replaceable neutral lens		1	30/60
GW 21 529	1P NO - 10A illuminable	With replaceable neutral lens		1	30/60
GW 21 531	1P NC - 10 A illuminable	With replaceable neutral lens		1	15/30
GW 21 519	1P NC - 10A	Neutral	Circle	1	15/30
GW 21 520	1P NO+NO - 10A	With interlock	Double circles	1	15/30
GW 21 521	1P NO+NO - 10A	With interlock	UP - DOWN	1	30/60
GW 21 522	1P NO - 10A - Aux. NC	Start	Green	1	30/60
GW 21 523	1P NC - 10A - Aux. NO	Stop	Red	1	30/60
GW 21 517	2P NO - 10A	Neutral	Double circle	1	30/60
GW 21 518	2P NO - 10A	With pull-cord		1	20/40
GW 21 530	2P NO - 10A	With key	0/1	1	15/30

CHARACTERISTICS: the illuminable articles use miniature lamp units, not included; GW21520, GW21521, both contacts are open in the central position (OFF).

ACCESSORIES SUPPLIED: GW21515 - red fluorescent 230Vac (0.4W) signalling unit. GW21516 - white LED 12/24Vac/dc (0.4W) signalling unit. GW21518, cord in insulating material, 140cm long, with a knob. GW21530 supplied with 2 keys. Spare keys: GW30912.



GW 21 024

PUSH-BUTTON WITH ILLUMINABLE NAME PLATE - 250V AC

Code	Description	Lamp voltage	Lamp	Lamp power	No. SYSTEM modules	Pack Carton
GW 21 591	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm	2 W	2	15/30
GW 21 024	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm	2 W	3	20/40

CHARACTERISTICS: supplied without lamp.



GW 21 589

WIDE-BUTTON ILLUMINABLE CONTROL DEVICES - 2M - 250V AC

Code	Description	Button key	Type	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 21 589	1P - 16 AX - illuminable	With diffuser	Two-way switch	200 W	2	15/30
GW 21 580	1P - 16 AX - illuminable	With diffuser	Intermediate switch	200 W	2	1/15
GW 21 527	1P NO - 10 A - illuminable	With diffuser	Push-button		2	15/30

CHARACTERISTICS: the illuminable articles use miniature lamp units, not included.

BLANKING MODULES AND CABLE OUTLET




GW 21 056

BLANKING MODULES AND CABLE OUTLET

Code	Description	No. SYSTEM modules	Pack Carton
GW 21 056	1 gang	1	10/480
GW 21 073	2 gang	2	30/60
GW 21 058	1 gang with outlet for cable Ø 4 and Ø 8mm	1	60/120

APPLICATIONS: in addition to their normal use, they permit installing signal socket-outlets, microswitches and LEDs after appropriate drilling/preparation.

LENSES WITH ILLUMINATED SYMBOL



SYMBOLS FOR ILLUMINABLE SWITCHES AND PUSH-BUTTONS

Code	Description	Symbol	Pack Carton
Suitable for: General services			
GW 20 533	Neutral		20
GW 20 537	Open door	Key	20
GW 20 538	Bell	Bell	20
GW 20 539	Light	Light	20
GW 20 540	Stair light	Stairs	20
GW 20 542	Service		20
Suitable for: Technical services			
GW 20 549	Dimmer		20
GW 20 550	Ventilation/Extraction		20
GW 20 551	Monitor/TV		20
GW 20 592	Opening arrows	Opening arrows	20
GW 20 593	Closing arrows	Closing arrows	20
GW 20 594	Off	OFF	20
GW 20 595	On	ON	20
GW 20 596	Up arrow		20
GW 20 597	Down arrow		20
Suitable for: Numerical services			
GW 20 561	One	1	20
GW 20 562	Two	2	20
GW 20 563	Three	3	20
GW 20 564	Four	4	20
GW 20 565	Five	5	20
GW 20 566	Six	6	20
GW 20 567	Seven	7	20
GW 20 568	Eight	8	20
GW 20 569	Nine	9	20
GW 20 570	Zero	0	20

NOTES: to be used in place of the neutral lens supplied with the illuminable command devices.

MOVEMENT SENSOR



GW 21 821

IR MOVEMENT DETECTOR

Code	Supply voltage	Output contacts	No. SYSTEM modules	Pack Carton
GW 21 821	230V ac - 50/60Hz	1NO 3A(AC1) 250V ac	1	1/6

CHARACTERISTICS: adjustment of the intervention duration 15 sec - 10 min. Light sensitive threshold adjustment - min. 10 lux - max. inhibited. Sensor with fixed lens. Suitable for commanding halogen lamps/resistive loads: 700 W, incandescent lamps: 450 W, low voltage halogen lamps (12 V) controlled by toroidal or electronic transformers: 450 W, uncompensated fluorescent lamps: 2x58 W, motors and gear motors: 400 VA. Not suitable for compensated fluorescent lamps, for discharge lamps and for all loads not indicated that must be commanded using a support relay.

APPLICATIONS: Energy-saving: command of the lighting of rooms and areas only when people pass through.

Comfort and safety: automatic command of circuits without needing to activate one-way switches.

NOTES: do not install the product in watertight plates: the lid membrane does not allow the detector lens to work correctly.