

# Product sheet

## Basic Information

Order Number  
Type  
Common Number




**2305032010**  
**W-CABLE**  
**S5378**



8592920026922

Measuring Unit  
Packaging  
Net Weight [kg]  
Dimensions [mm]  
Technical Support

KS  
1 / - / - / 1000  
0.02  
10 × 120 × 255  
Petr Veselý, 581261172,  
vesely@emos.cz



## Basic Product Description

Window bushing designed for leading coaxial cables through the window without the need for drilling. A practical method of laying cables, quick and simple. The bushing is fitted on both ends with handy F connectors.

## Technical Description

coaxial cable type  
impedance  
intended use  
UV resistant  
suitable for outdoor use  
material of the inner  
conductor  
diameter of the inner  
conductor  
dielectric type, diameter  
number of shieldings  
material of the shielding  
number of braiding wires  
shielding diameter

3C2V  
75 Ohm  
replacement of drilling of the walls  
yes  
yes  
copper (Cu)  
0.5 mm  
PE 1.6 mm  
1  
copper clad aluminium (CCA)  
32× 0.12 mm  
32× 0.12 mm²

## Product sheet

shielding protection	28 %
diameter of cable sheath	3 mm
material of the cable jacket	PVC
color cable sheath > Cable sheath color	white
capacity (pF/m)	53
factor of shortening	0.81
storage temperature	-20 °C to +75 °C
mounting temperature	+5 °C to +60 °C
type of packaging - length	22 cm
reaction to the fire	do not subject to CPR
dangerous substances	do not subject to CPR
packaging	1 pc, PE packet
warranty period	2 years