

GV3A03

TeSys GV3 - auxiliary contact - 2 NO + 1 NC early-break

Product availability : Non-Stock - Not normally stocked in distribution facility



Price** : 45.00 USD



Main

Range	TeSys
Device short name	GV3A
Product or component type	Auxiliary contact block
Product compatibility	GV3ME
Mounting location	Right side
Pole contact composition	2 NO + 1 NC
Connections - terminals	screw clamp terminals 1 0.00...0.00 in ² (1...2.5 mm ²)solid screw clamp terminals 2 0.00...0.00 in ² (1...2.5 mm ²)solid screw clamp terminals 1 0.00...0.00 in ² (0.75...2.5 mm ²)flexible without cable end screw clamp terminals 2 0.00...0.00 in ² (0.75...2.5 mm ²)flexible without cable end screw clamp terminals 1 0.00...0.00 in ² (0.75...2.5 mm ²)flexible with cable end screw clamp terminals 2 0.00...0.00 in ² (0.75...1.5 mm ²)flexible with cable end
Quantity per set	Set of 10

Complementary

[Ui] rated insulation voltage	600 V UL 508 690 V IEC 60947-1 600 V CSA C22.2 No 14
[Ue] rated operational voltage	48...690 V AC 24...220 V DC
[Ith] conventional free air thermal current	6 A
Protection type	GB2CB... circuit breaker GG fuse 6 A
Mechanical durability	100000 cycles
Rated operational power in VA	350 VA 48 V AC-11 100000 cycles 700 VA 440 V AC-11 100000 cycles 700 VA 500 V AC-11 100000 cycles 400 VA 690 V AC-11 100000 cycles 500 VA 110...127 V AC-11 100000 cycles

	800 VA 220...240 V AC-11 100000 cycles 850 VA 380...415 V AC-11 100000 cycles
Rated operational power in W	180 W 24 V DC-11 100000 cycles 240 W 48 V DC-11 100000 cycles 180 W 60 V DC-11 100000 cycles 140 W 110 V DC-11 100000 cycles 120 W 220 V DC-11 100000 cycles
Net weight	0.15 lb(US) (0.07 kg)

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

Ordering and shipping details

Category	22366 - MAN STR PROTECTORS-GV1/GV3
Discount Schedule	I11
GTIN	00785901494997
Returnability	No
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------