

PRODUCT DATASHEET LED BULB FA-15W/A70/865L E27

Consumer Products LED Bulb A | LED lamps, classic bulb shape



AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time
- Poly covered aluminium housing with better heating diffusion
- Built-in constant current driver better stability of usage

PRODUCT FEATURES

- LED alternative to conventional lamps
- Mercury-free lamps




TECHNICAL DATA


Electrical data

Rated wattage	15.00 W
Nominal wattage	15.00 W
Nominal voltage	185-240VAC
Operating frequency	5060 Hz
Power factor \(\lambda \)	> 0.50
Claimed equiv. conventional lamp power	120 W

Photometrical data

Rated luminous flux	1500 lm
Light color (designation)	Cool White
Color temperature	6500 K
Luminous flux	1500 lm
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	1500 lm
Rated color temperature	6500 K
Color rendering index Ra	≥80






Light technical data

Starting time	< 0.5 s
Beam Angle	260°

Dimensions & weight



Overall length	135.0 mm
Diameter	70.0 mm
Outer bulb	A70
Length	135.0 mm

Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	15000
Warranty	2 years

Capabilities

Dimmable	No
----------	----

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	98 °C

Additional product data

Base (standard designation)	E27	
Mercury-free	Yes	
Design / version	frosted	
Driver type	IC	
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	
Mercury content	0.0 mg	
Standards	CE/CCC	

Order code/Name

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
FA2435	Folding carton box 1	70 mm x 70 mm x 130 mm	80.00 g	0.63 dm³
FA2435	Shipping carton box 100	730 mm x 370 mm x 280 mm	8200.00 g	0.080 m³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping

REFERENCES / LINKS

For further products and actual information concerning LED lamps see www.fucida.eu

For Guarantee see www.fucida.eu

DISCLAIMER

Subject to change without notice. Errors and omission excepted.