

# Technical Data Sheet

Rust-Oleum Universal All Surface Paint (400ml spray):

Black (Gloss, Satin, Matt), White (Gloss, Satin, Matt), Slate Grey (Gloss), Cobalt Blue (Gloss), Racing Green (Gloss), Espresso Brown (Gloss), Crimson Red (Gloss), Cardinal Red (Gloss), Sunset Orange (Gloss), Canary Yellow (Gloss), Real Almond (Gloss), Black (Hammered), Brown (Hammered), Copper (Hammered), Pure Gold (Metallic), Titanium Silver (Metallic), Satin Nickel (Metallic), Aged Copper (Metallic) & Oil Rubbed Orange (Metallic).

---

**Rust-Oleum Universal is a premium all surface paint that provides the ultimate long-lasting protection and durability. The breakthrough formulation delivers exceptional coverage on plastic, wood, metal, concrete, wicker, aluminium and masonry surfaces. It features an advanced spray system that allows you to spray at any angle, even upside down for those hard to reach areas. Stops rust. Paint & primer in one.**

## Interior or Exterior:

**Preparation:** Ensure surfaces to be painted are free from loose paint, rust, wax, oil and grease. Previously painted surfaces should be abraded to provide a key. Cover surrounding areas to protect from spray mist.

**Application:** Shake can vigorously for 1 minute after mixing ball begins to rattle, continue to shake regularly during use. Hold can 30cm from surface and spray in a steady back and forth motion, slightly overlapping with each stroke. For best results whilst spraying keep the can the same distance from the surface and keep the can in motion. Apply several light coats a few minutes apart.

**Cleaning:** Wipe wet paint from nozzle with white spirit.

**Drying & Recoating:** Touch dry in 30 minutes. Hard dry in 24 hours.

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK.

**Technical Services Department: 0191 410 6611**

E-mail: [info@tor-coatings.com](mailto:info@tor-coatings.com) [www.tor-coatings.com](http://www.tor-coatings.com) or [www.rustoleumspraypaint.com](http://www.rustoleumspraypaint.com)

Recoat within 1 hour or after 24 hours. 1-2 coats recommended.

**Coverage:** A 400ml can covers approximately 2m<sup>2</sup> dependent upon surface profile / porosity.

**Limitations:** Do not use on galvanised steel or surfaces that regularly exceed temperatures over 90°C. Apply only when temperature is between 10-32°C and relative humidity below 85%.

Special precautions should be taken during the surface preparation of pre 1960's paint surfaces over wood and metal as they may contain harmful lead. When dry-sanding avoid dust inhalation by wearing a suitable protective face mask. A copy of the appropriate Health & Safety should be consulted prior to use. For further information please contact our Technical Services Department.

**Shelf Life:** 3 years (unopened) from date of manufacture. (See base of can).

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.