





















 <p>HERRINGBONE</p>		150x750	MICRO BEVEL	STANDART	
		PACKAGE(m ²)	PALETTE(m ²)	CONTAINER(20')	WARRANTY(Year)
		16 X  =1.800 m ² =14.40 Kg	77 X  =138.600 m ² =1.108.80 Kg	22 X  =3.049.20 m ² =24.393.60 Kg	15

Technical Specification

	Surface treatment (UV)		YES
	Underlay	IXPE	1mm
	Thickness in Total	ISO24337	5mm
	Thickness of wear layers	EN429	0.3mm
	Weight in total	EN ISO 23997	8,0 kgs/sqm
	Dimension Stability	TS EN ISO 23999	Class 34
	Performance classification	23,34,43	
	Residual indentation after static load	TS EN ISO 24343-1:2007	0.01mm
	Slip Resistance	EN13893	DS
	Electrostatic Behaviour	1815:2016	Antistatic Floor Covering
	Floor Heating System	Suitable	Max.27 ⁰ C
	Antibacterial	ISO22196	Antibacterial
	Phatalate Analysis	Inhouse Method	Phatalate Free
	Emission of Formaldehyde	EN 717-1:2004	E1
	Fire Behaviour	EN13501-1 EN 9239-1:2010	BFL-S1
	Reaction to Fire	EN 11925-2:2020	B-s1-d0
	Thermal Resistance	EN 12667	0.296 W/(m.K)



ISO 9001:2015
ISO 14001:2015

