

Date tehnice / Technical data

Cod produs / Product's code	681290
Tip motor / Engine	OHV, 4 timpi, 1 cilindru racit cu aer / OHV, 4 stroke, air cooled monocylinder
Capacitate cilindrica / Displacement	93 cm ³
Putere maxima / Max power	2,0 CP / 3600 rpm
Tip generator electric / Electric generator	monofazat / single phase
Tensiune / Frecventa generate / Generated voltage / frequency	230 V / 50 Hz
Putere electrica generata (S1) / Generated electric power (S1)	900 W
Putere electrica maxim generata (S2) / Max generated electric power (S2)	1000 W
Timp de functionare continua / Continuous working time	6 h
Timp de functionare putere maxima (S2) / Max power working time (S2)	5 min
Priza CA 230 V / 230 V AC socket	1 priza / 1 socket
Factor de putere cos φ / Power factor	1
Altitudine maxima de folosire / Max altitude	1000 m
Combustibil / Fuel	Benzina fara Pb min 95 / Non-leaded gasoline min 95
Volum rezervor combustibil / Fuel tank volume	7 L
Ulei* / Oil*	SAE 10W-30
Volum ulei / Oil volume	~500 mL
Nivel maxim de zgomot / Max sound power	LwA = 81 dB(A), K = 3 dB(A)
Masa neta / Net weight	~ 24 kg

*Folositi numai ulei HGT destinat motoarelor in 4 timpi, norma SAE 10W-30 / Use only HGT oil designed for 4 stroke engines, type SAE 10W-30.