

PATCH Cable CAT 5E UTP, 15m**Product sheet****Basic Information**

Order Number
Type
Common Number

2309010070
UTP CAT5E PVC 15M
S9127






8595025385536



Measuring Unit
Packaging
Net Weight [kg]
Dimensions [mm]
Technical Support

KS
1 / - / 5 / 20
0.307
40 × 200 × 200
Petr Veselý, 581261172,
vesely@emos.cz

**Basic Product Description**

Unshielded patch cable of category CAT5E with moulded protection.

Technical Description

warranty period	5 years
product	cable with connectors
connectors	RJ45/RJ45
connector protection type	cast
type	UTP CAT 5E 15M
length	15 m
cable structure	stranded wires
category	5E
material of the inner conductor	copper clad Al (CCA)
AWG	26
inner conductor diameter	0.53 mm
wire insulation	HDPE
conductor insulation thickness	0.22 mm
strength member	Nylon 150D

Product sheet

cable sheath	PVC
jacket diameter	5 mm
jacket thickness	1.1 mm
sheath color	grey (RAL 7035)
marking of cable	UTP Cat5E PVC Patch cable
highest supported protocol	1000 Base-T (Gigabit Ethernet)
storage temperature	-20 °C to +60 °C
mounting temperature	+5 °C to +60 °C
maximum operating humidity	93 %
reaction to the fire	do not subject to CPR
dangerous substances	do not subject to CPR
number of wires	8
packaging	1 pc, PVC packet